

2" Koto Sylo™ Pendant

Works with Koto™ Standard LED Module



Features

- Modern Die-Cast aluminum fixture for easy maintenance and upgrades
- Available with 120" Field Cuttable Cable or Stems (12", 24", 36", 48", 60", 72" and 84")
- Includes Standard 38° lens, with 25° and 60° lenses. Optional: 18° & 90° lenses available.
- Fits 3 1/2" and 4" Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- Tunable White option dims from 1800K to 4000K
- Human Centric option dims from 4000K to 2200K
- Energy Star Certified. Title 24 JA8-2022 Compliant
- Life span of 50,000 hours L70
- **120V Triac/ELV** with standard module options (-03, -07, -08, -09, -10, -11, -13 series)
120/277V, 0-10V/Triac/ELV with DX module (-10DX series)

Specifications

Wattage	10.5W
Lumens	750 lm
Voltage	120V
Color Temp.	3500K
Dimmable	Triac/ELV
Lamp Type	LED
Beam Angle	38°
CRI	95

Options



Technical Details

Optics: Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Construction: Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

Installation: Twist-on design for toolless trim installation, for use with Koto Sylo™ products only.

Electrical: Module connects to 120 power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.

LED Technology: Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Delivered Lumens:


0327 2700K/442.8 lm/5W **0330** 3000K/461.2 lm/5W

0727 2700K/770 lm/10.5W **0730** 3000K/800 lm/10.5W **0735** 3500K/830 lm/10.5W **0740** 4000K/860 lm/10.5W

08CT5 2700K/728.5 lm/10.5W **08CT5** 3000K/886 lm/10.5W **08CT5** 3500K/902 lm/10.5W
08CT5 4000K/920 lm/10.5W **08CT5** 5000K/931 lm/10.5W

0927 2700K/912 lm/10.5W **0930** 3000K/950 lm/10.5W **0935** 3500K/990 lm/10.5W **0940** 4000K/1030 lm/10.5W **09SD** Sunset/940 lm/10.5W

Dimensions



Dimensions with Stem



10CTS 2700K/908 lm/12.5W **10CTS** 3000K/1012 lm/12.5W **10CTS** 3500K/1038 lm/12.5W
10CTS 4000K/1040 lm/12.5W **10CTS** 5000K/1032 lm/12.5W

10DX27 2700K/979 lm/11.8W **10DX30** 3000K/1020 lm/11.8W **10DX35** 3500K/1060 lm/11.8W **10DX40** 4000K/1103 lm/11.8W **10DXSD** Sunset/1000 lm/11.8W

1124 2400K/730 lm/12.5W **1127** 2700K/1068 lm/12.5W **1130** 3000K/1112 lm/12.5 **1135** 3500K/1156 lm/12.5W **1140** 4000K/1202 lm/12.5W **11SD** Sunset/1050 lm/12.5W **11HC** Human Centric/1050 lm/12.5W

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatibility List. Industry-leading dimming that dims smoothly with no hot spots or flickering.

Listings: cUL Listed for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2022 standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Number Builder Example: **E25PW-0727**

Koto Sylo™	Style	Finish	Koto™ Module	Color Temperature	Beam Angle	Length
E25						
	P Pendant	W All White B All Black S Silver	-03 350 lm (5W) ^{1, 2} -07 750 lm (10.5W) ¹ -08 825 lm (10.5W) ^{1, 3} -08AL 850 lm (11.5W) ⁴ -09 950 lm (10.5W) ¹ -10 1000 lm (12.5W) ^{1, 3} -11 1150 lm (12.5W) ¹ -10DX 1000 lm (11.8W) ⁵ -13 1350 lm (12.5W) ¹	24 2400K 27 2700K 30 3000K 35 3500K 40 4000K SD Sunset (-09 and -11 only) ^{6, 7} HC Human Centric (-11 only) ^{8, 9} CT5 2700K - 5000K ^{10, 11} 4T Tunable White 4000K-1800K ¹²	38º lens ¹³ -S 18º lens -N 25º lens -W 60º lens -T 10º lens ^{10, 14} -E 90º lens ¹⁵	120" Cable Mount ¹⁶ -12 12" Stem ¹⁷ -24 24" Stem ¹⁷ -36 36" Stem ¹⁷ -48 48" Stem ¹⁷ -60 60" Stem ¹⁷ -72 72" Stem ¹⁷ -84 84" Stem ¹⁷

¹ Available as 120V, Triac/ELV only

² Available with 2400K, 2700K and 3000K Color Temperature Only

³ Available with CT5 color temperature only

⁴ DALI 2, 120/277V

⁵ 120/277V, 0-10V/Triac/ELV

⁶ Available in -09, -11, & -13 lumen outputs

⁷ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

⁸ Available with 1150 lumen (-11) outputs only

⁹ Human Centric, Dim to Warm technology, automatically transitions from 4000K to 2200K when dimmed

¹⁰ Available as 120V, Triac/ELV only

¹¹ Available with -08 and -10 lumen outputs only

¹² Available with -AL option only, Dali 2 dimmable Tunable White

¹³ Includes 25° and 60° lens in the box

¹⁴ Available with 350 and 750 lumen, 2700K and 3000K options only

¹⁵ 90° Frosted Reflector

¹⁶ 120 inch field cuttable cable

¹⁷ Stem is not field cuttable

Compatible Products

For use with Dedicated **Koto Sylo™** Fixtures



Junction Boxes for Koto Sylo™ Ceiling Mount Fixtures



3 1/2" & 4" Octagon
Steel Junction Boxes

4" x 4" x 1 1/2"
4" x 4" x 2 1/8"
3 1/2" x 3 1/2" x 1 1/2"



4" Round Surface
Mount Box

4" O.D. x 1 1/2"



3 1/2" Round Old Work
(Non-Metallic)

4 1/4" O.D. x 3 1/2" I.D. x 2 5/8"



3 1/2" & 4" Round New Work
(Non-Metallic)

4" O.D. x 2 3/16"
3 1/2" O. D x 2 3/4"

Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-ERT	25W, 120/277V

Koto™ LED Module Accessories



Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens

**EP732C, EP733C, EP734C Included*



Reflectors

EP735C 15°
EP736C 25°
EP737C 38°
EP738C 60°



Secondary Optics

L45 Hex Louver
L46 Linear Louver
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter



Snoot

L50W White
L50B Black

Photometric Report

2" Koto Sylo™ Pendant Koto™ LED Module

PHOTOMETRIC REPORT

Product #: E25PW-0330
Wattage / Lumens: 5.4W / 462.2 lm
Luminaire LPW: 85.6 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2530
5	1613
15	294
25	34
35	14
45	9
55	7
65	7
75	4
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	158	1.4'
6'	70.3	2.1'
8'	39.5	2.8'
10'	25.3	3.5'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	405.4	87.8
0-40°	417.6	90.5
0-60°	433.0	93.8
0-90°	447.5	96.9

PHOTOMETRIC REPORT

Product #: E25PW-08CT5 (3000K)
Wattage / Lumens: 10.19W / 887.3 lm
Luminaire LPW: 87 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1904
5	1681
15	902
25	250
35	61
45	30
55	17
65	10
75	6
85	6
90	6

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	119	2.6'
6'	52.9	3.9'
8'	29.7	5.1'
10'	19.0	6.4'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	702.7	79.2
0-40°	771.5	87
0-60°	819.9	92.5
0-90°	845.8	95.4

PHOTOMETRIC REPORT

Product #: E25PW-10CT5 (3000K)
Wattage / Lumens: 12 W / 1013.2lm
Luminaire LPW: 84.4 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2241
5	2012
15	1152
25	323
35	77
45	35
55	20
65	11
75	7
85	5
90	6

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	140	2.6'
6'	62.2	3.9'
8'	35.0	5.2'
10'	22.4	6.5'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	816.5	80.6
0-40°	893.2	88.2
0-60°	947.2	93.5
0-90°	973.3	96.1

PHOTOMETRIC REPORT

Product #: E25PW-10DX27
Wattage / Lumens: 12W / 978.5 lm
Luminaire LPW: 81.5 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2503
5	2261
15	1250
25	246
35	63
45	34
55	24
65	14
75	6
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	156	2.3'
6'	69.5	3.5'
8'	39.1	4.7'
10'	25.0	5.8'

ZONAL LUMEN SUMMARY


Zone	Lumens	%Luminaire
0-30°	846.4	86.6
0-40°	905.4	92.6
0-60°	955.8	97.8
0-90°	977.5	100

Photometric Report

2" Koto Sylo™ Pendant Koto™ LED Module

PHOTOMETRIC REPORT

Product #: E25PW-1127
Wattage / Lumens: 12.5W / 1086.2 lm
Luminaire LPW: 86.9 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	1606
5	1542
15	1297
25	723
35	338
45	128
55	42
65	17
75	8
85	3
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	100	3.2'
6'	44.6	4.8'
8'	25.1	6.4'
10'	16.1	7.9'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	757.2	70.6
0-40°	933.9	87.1
0-60°	1,045.2	97.5
0-90°	1,066.1	99.4

PHOTOMETRIC REPORT

Product #: E25PW-1130
Wattage / Lumens: 11.8W / 1162.5 lm
Luminaire LPW: 98.5 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	3043
5	2807
15	1766
25	520
35	98
45	46
55	34
65	22
75	12
85	8
90	6

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	190	2.4'
6'	84.5	3.6'
8'	47.5	4.7'
10'	30.4	5.9'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	997.9	85.9
0-40°	1,064.7	91.6
0-60°	1,125.3	96.9
0-90°	1,161.6	100

PHOTOMETRIC REPORT

Product #: E25PW-1135
Wattage / Lumens: 11.8W / 1210 lm
Luminaire LPW: 102.5 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	3164
5	2920
15	1836
25	540
35	102
45	47
55	35
65	23
75	13
85	8
90	7

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	198	2.4'
6'	87.9	3.6'
8'	49.4	4.7'
10'	31.6	5.9'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	1,037.8	85.9
0-40°	1,107.3	91.6
0-60°	1,170.3	96.9
0-90°	1,208.1	100

PHOTOMETRIC REPORT

Product #: E25PW-1330
Wattage / Lumens: 11.8W / 1312.2 lm
Luminaire LPW: 111.2 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	1575
5	1497
15	1224
25	824
35	377
45	142
55	35
65	9
75	2
85	1
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	98.4	4.0'
6'	43.8	6.0'
8'	24.6	8.0'
10'	15.8	10.0'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	879.8	67.1
0-40°	1,140.2	86.9
0-60°	1,298.7	99
0-90°	1,311.4	100



ELCO Lighting

Dimmer Compatibility Chart

Standard Koto™ LED Modules

For ELK07, ELK08CT5, ELK09, ELK10CT5,

ELK11 & ELK13 Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	Decora SureSlide® Single Pole with Slide -to-Off	6672	15% - 100%
	Leviton Dimmer	1K3502	5% - 100%
Lutron	Vive, 120V, 150W LED/CFL, 600W Incandescent/Halogen, FP, Single Pole/Multi-Location Dimmer, Commercial Application	MRF2S-6CL	12% - 91%
	Panel Model, Commercial/Residential Application, FP	GP (Harrier) Card	10% - 94%
	Grafik QS/Mailbox Power Module, 120/220 to 240V AC, LED/Incandescent/Halogen Load Type, Commercial/Residential Indoor Application, FP	LQRJ-WPM-6P	10% - 95%
	Grafik Eye 3000/HomeWorks, 120V, Incandescent/Fluorescent Load Type, Commercial/Residential Application, FP	HWI-WPM-6D-120	10% - 95%
	Panel Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4U-120	10% - 95%
	Panel Adaptive Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4A-120	9% - 95%
	HomeWorks® QS for CFL/LED loads, 120V, RP, Commercial/Residential Application	LQSE-4A1-D/MQSE-4A1-D/ MQSE-3A1/MQSE-2A1-D	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Reverse Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Foward Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	10% - 97%
	RadioRA®2, 120V, 50/60-Hz, 150W LED or 600W Incandescent/Halogen, 3-Way & 4-Way, Residential Application	RRD-6CL	10% - 95%
	RadioRA®3, 120V, 250W LED/CFL or 500W Incandescent/Halogen, Single Pole, Multi-Location	RRST-PRO-N	10% - 95%
	HomeWorks® QS, 120V, 60-Hz, 150W LED/CFL or 600W Incandescent/Halogen/MLV, Residential Application	HQRD-6CL(H2) HORA-6CL(H2)	10% - 95%
	Homeworks QS, Residential Application, Reverse Phase	LQSE-4A-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Reverse Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Foward Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	10% - 100%
	Ariadni® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	AYCL-153P	10% - 100%
	Skylark Contour® C-L, Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	CTCL-153P	10% - 100%
	Skylark® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	SCL-153P	10% - 100%

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Diva® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
	Skylark Contour® Single Pole/3-Way 1000W Incandescent/Halogen	CT-103P	10% - 100%
	Skylark® Single Pole 300W ELV Preset Dimmer	SELV-300P	5% - 100%
	Skylark® Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer	S-600P	5% - 100%
	Diva® 300W Single Pole/3-Way ELV Dimmer	DVELV-303P	10% - 100%
	Diva® 600W Single Pole Incandescent/Halogen Preset Dimmer	DV-600P	5% - 100%
	Ariadni® 600W Single Pole Magnetic Low Voltage Dimmer	AYLV-600P	5% - 100%
	Ariadni® 600W Single Pole/3-Way Incandescent/Halogen Dimmer	AY-603P	5% - 100%
	Maestro® 600W Single Pole/3-Way ELV Dimmer	MAELV-600	5% - 100%
	Maestro® C-L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Max for Incandescent/Halogen	MACL-153M	10% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	10% - 100%
SnapOne™	Control4® Centralized 8-Channel Adaptive Phase Dimmer, 120/277V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/ELV/MLV*	C4-DIN-8APD	5% - 100%
	Control4® Centralized 8-Channel Forward Phase Dimmer, 100/120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen/MLV*	C4-DIN-8FPD	25% - 100%
	Control4® Wireless Adaptive Phase Dimmer, 120V AC, 50/60-Hz, 120W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-APD120	23% - 100%
	Control4® Forward Phase Dimmer, 120V AC, 50/60-Hz, 200W LED, 500W Fluorescent/CFL, 1000W Incandescent/Halogen	C4-FPD120	4% - 100%
	Control4® Essential Forward Phase Dimmer, 120V AC, 60-Hz, 300W LED, 300W Fluorescent/CFL, 600W Incandescent/Halogen	C4-V-FPD120	1% - 100%

*MLV each transformer must be loaded to at least 50% of its maximum load

***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com