

24V DC 4" Shallow Max. Adjustability New Construction IC Airtight Housing



24V DC 4" MAX. Adjustability New Construction Housing. Compatible with 24V DC Koto™ Module.


Features

- Only for use with [24V DC Koto Module](#)
- IC Airtight for direct contact with insulation
- Simple installation with 24V Wire
- 24V DC Quick Connect for easy module installation
- Integrated collar allows for use with 3/8" thick to 1 1/2" thick ceilings
- Limited 5 year warranty

Specifications

Voltage	24V DC
Dimmable	Triac/ELV

Dimensions



Technical Details

Construction:

- IC rated for direct contact with insulation, for use in IC or non-IC conditions.
- Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness.
- Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.
- Steel housing for greater heat dissipation. Stamped galvanized steel frame.

Installation: Designed for ceiling plenums where 2x6 joists or taller joists are used. High strength swivel hanger bars can easily be nailed to joists. Maximum hole cutout is 4 1/4". Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts, four 3/4" knockouts with pry-out knockout slots. 4 Romex pryouts with strain relief.

Hanger Bars: Pre-installed swivel hanger bars with TrueNail facilitate easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while aligning the housings with the joists.

Electrical:

- Input Voltage: 24V DC.
- Inherently protected.

Dimmability:

- Dimmability based on driver.

Lamp: Designed for use with ELCO 4" PEX Diecast Trims and 24V DC Koto™ LED module

Listings:

- cULus Listed for US and Canada.
- cUL Listed for Damp Location.
- cUL Listed for Wet Location with select trims.
- cUL Listed for Feed Through.
- cUL Listed for Direct Contact with Insulation and Combustible Material.
- Airtight per ASTM E-283.
- Install a JA8-2022-E lamp for Title 24 Compliance.

Warranty: ELCO Lighting warrants products will be free from defects in materials and workmanship for a period of 5 years.

Product Numbers

Item	Description	Voltage	Dimming
E24V453ICA	Shallow MAX. Adjustability Housing	24V DC	Triac/ELV

