ELCO Lighting

Project name:

Fixture type:

Date:

3″ Knife Edge Wood Ceiling Trim

With Mounting Clips for use with Round Flush Mount Koto Trim Adaptor

Features

- Compatible with 3″ Adjustable Trimless Reflector (ELK315) and with 3″ Fixed Trimless Reflector (ELK308). Sold Separately
- 3″ Die-Cast Round Adaptor with Mounting Clips.
- Compatible with ceilings up to 2″ thick
- 3 7/8″ O.D.
- Lamp: Koto™ LED Module and Canless Koto™ LED Module.
- **For use only with EL386ICA, architectural Koto housings or with 3" Koto canless**

Technical Details

Construction: Diecast aluminum with a powder-coated finish.

Installation: For use with 3″ Trimless Smooth Reflector (ELK315W) or with 3″ Fixed Trimless Reflector (ELK308). Sold separately. Compatible with ceilings up to 2″ thick. Remove collar from housing before installing.

Lamp: Koto™ LED Module and Canless Koto™ LED Module.

Options

White **Black**

Dimensions



Product Numbers

Item	Finish
EL3WCRW	All White
EL3WCRB	All Black

Product Number Builder Example: **EL3WCRW**

3″ Canless Knife Edge Wood Ceiling Trim	Color Finish
EL3WCR	

W All White
B All Black

© ELCO Lighting 2026. All rights reserved • Rev. 06 Oct 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **3" Koto™ Twist-&-Lock Trimless**

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	**27** 2700K	**(blank)** 38° lens (Standard)
	09 950 lm	**30** 3000K	**-S** 18° lens
	11 1150 lm	**35** 3500K	**-N** 25° lens
		40 4000K	**-W** 60° lens
		SD Sunset Dimming (For ELK09 & ELK11)	**-FC** 18° - 50° Adjustable (ELK07 Only)



Koto™ LED Module with 5-CCT Switch

Product Number

ELK08CT5	825 lm
ELK10CT5	1000 lm

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Snoot

L50W	White
L50B	Black



Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L51	Color Shifter

3" Koto™ Dedicated LED ICA Housings



3" ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability

3" Pex™ Trimless

Round Trimless Reflector
ELK308
Finishes:
(W, B, H)

Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

© ELCO Lighting 2026. All rights reserved • Rev. 06 Oct 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **3" Koto™ Twist-&-Lock Trimless**

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 750 - 850 lm	**27D** 2700K	**(blank)** 38° lens (Standard)
	21 1100 - 1500 lm	**30D** 3000K	**-S** 18° lens
		35D 3500K	**-N** 25° lens
		40D 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK19 Only)	**-FC** 18° - 50° Adjustable (ELK21 Only)

ACCESSORIES

Lens
EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens
**EP732C, EP733C, EP734C Included*

Snoot
L50W White
L50B Black

Secondary Optics
L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter

3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK53ICA	15.7W - 120V - Triac/ELV
E3LK54ICAD	15.7W - 120/277V 0-10V/Triac/ELV
E3LK85ICAD	18.9W - 120/277V 0-10V/Triac/ELV



3" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV

3" Pex™ Trimless

Round Trimless Reflector
ELK308
Finishes:
(W, B, H)



Adjustable Trimless Reflector
ELK315
Finishes:
(W, B, H)

© ELCO Lighting 2026. All rights reserved • Rev. 06 Oct 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.