

# 3" Koto™ Architectural Shallow Maximum Adjustability IC Airtight Housing



Koto™ Architectural Housing: 120/277V (0-10V/Triac/ELV) or 120V (Triac/ELV), and ICALWN (Lutron Athena Wireless Node) with optional Emergency Battery Backup. Must be used with Koto™ Architectural LED Light Engines (ELK19, ELK21, or ELK24 Series). Lumen output based on module.

## Features

- IC Airtight for direct contact with insulation.
- Easy-to-Remove driver.
- Optional 90 minutes, 120/277 VAC, 60Hz, Emergency Backup.
- Flicker-Free Dimming.
- USA designed and assembled.
- Limited 5 year warranty.
- For use with ELCO Koto™ Architectural LED Light Engines (ELK19, ELK21, or ELK24 Series).

## Specifications

|                      |                                              |
|----------------------|----------------------------------------------|
| <b>Wattage</b>       | 14.7W                                        |
| <b>Lumens</b>        | 850 (ELK19) - 1100 (ELK21) - 1500 (ELK24) lm |
| <b>Voltage</b>       | 120V                                         |
| <b>Dimmable</b>      | Triac/ELV                                    |
| <b>Lamp Type</b>     | LED                                          |
| <b>Power Factor</b>  | ≥0.95                                        |
| <b>Damp Location</b> | Listed                                       |

## Dimensions



## Technical Details

**Construction:** Single Wall IC Rated for direct contact with insulation. For use in IC and Non-IC conditions. Up to 1100 lumens. Housing adjusts in frame to accommodate up to 1 1/2" ceiling thickness. Airtight housing with gasket to restrict airflow in accordance with ASTM E-283 air-tight requirements.

**Installation:** Designed for ceiling plenums where 2x6 joists or taller are used. High strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. See installation sheet for detailed information. Emergency Battery Back-up Option requires access from above. For use with ELCO Koto™ Architectural LED Light Engines (ELK19, ELK21, or ELK24 Series).

**Junction Box:** Positioned to accommodate straight conduit runs. Two 3/4" knockouts, Seven 1/2" trade size conduit knockouts, One 3/8" knockout. Four Pry-out knockout slots for easy romex installation.

**Hanger Bars:** Pre Installed hanger bars with True Nail easy installation in regular lumber, engineered lumber, and Laminated Beams. Integral T-bar slots for easy installation in T-Bars. Spans up 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

**Electrical:** Driver is rated for 120V and 277V input (120/277V). High Efficiency driver with a power factor > 0.95.

**Emergency Battery Pack:** Optional 90 minute battery pack available with test indicator switch. Note that double wall housings require Access From Above Ceiling for Battery Maintenance.

**Dimmability:** 3-in-1 Dimming: Triac, ELV and 0-10V dimming in one driver. 0-10V Dimming down to 5% with a compatible dimmer. ICALWN - Lutron Athena Wireless Node. Can be specified with Lutron drivers for 0.1% and 1% dimming. For a full list of dimmers refer to the Dimmer Compatibility List.

**Listings:** cUL Listed for Damp Location and for Wet Location with select trims. cUL Listed for Direct Contact with Insulation and Combustible Material. cUL Listed for Feed Through.

## Product Number

| Item             | Description                           | Lamp type | Lumens                                       | Watts | Voltage | Dimming   |
|------------------|---------------------------------------|-----------|----------------------------------------------|-------|---------|-----------|
| <b>E3LK76ICA</b> | Shallow Maximum Adjustability Housing | LED       | 850 (ELK19) - 1100 (ELK21) - 1500 (ELK24) lm | 14.7W | 120V    | Triac/ELV |

Product Number Builder

Example: E3LK76ICA

|                             |                          |                               |
|-----------------------------|--------------------------|-------------------------------|
| Koto™ Architectural Housing | Voltage                  | Dimming                       |
| E3LK                        |                          |                               |
|                             | 76 120V <sup>1</sup>     | ICA Triac/ELV                 |
|                             | 77 120/277V <sup>2</sup> | ICAD 0-10V/Triac/ELV          |
|                             |                          | ICADAL DALI 2                 |
|                             |                          | ICAWAN Lutron Athena Wireless |

<sup>1</sup> Available as 120V, Triac/ELV only


<sup>2</sup> Available as 120/277V, 0-10V/Triac/ELV only

# Compatible Products

For use with Dedicated 3" Architectural ICA LED Housings



## Koto™ Architectural LED Light Engine



Koto™ LED Light Engine  
ELK21 & ELK24

| PRODUCT NUMBER BUILDER |                             |                   |                                       |
|------------------------|-----------------------------|-------------------|---------------------------------------|
| Koto™ LED Light Engine | Lumens                      | Color Temperature | Beam Angle                            |
| ELK                    |                             |                   |                                       |
| 21                     | 1100 - 1500 lm <sup>1</sup> | 27D 2700K         | (blank) 38° lens (Standard)           |
| 24                     | 1100 - 1800 lm <sup>1</sup> | 30D 3000K         | -S 18° lens                           |
|                        |                             | 35D 3500K         | -N 25° lens                           |
|                        |                             | 40D 4000K         | -W 60° lens                           |
|                        |                             |                   | -FC 18° - 50° Adjustable (ELK21 Only) |

<sup>1</sup>Wattage based on housing.

### ACCESSORIES



#### Lens

EP731C 18° Lens  
EP732C 25° Lens  
EP733C 38° Lens  
EP734C 60° Lens

<sup>\*</sup>EP732C, EP733C, EP734C Included



#### Snoot

L50W White  
L50B Black



#### Secondary Optics

L45 Hex Louver  
L46 Linear Lens  
L47 Spread Louver  
L49 Frosted Lens  
L51 Color Shifter

## 3" Pex™ Twist-&-Lock Trims



#### Deep Reflector

ELK3618

Finishes:

(W, BB, BZ, B, C, H)



#### Adjustable Gimbal

ELK3629

Finishes:

(W, BB, BZ, B, C, H)




#### Adjustable Pinhole

ELK3627

Finishes:

(B, BB, BZ)



#### Adjustable Baffle

ELK3693

Finishes:

(W)



#### Slot Aperture

ELK3620

Finishes:

(W)




#### Adj. Reflector Wall Wash

ELK3622

Finishes:

(W)



#### Sq. Deep Reflector

ELK3318

Finishes:

(W, BB, BZ, B, C, H)



#### Sq. Adjustable Gimbal

ELK3329

Finishes:

(W, BB, BZ, B, C, H)




#### Sq. Adjustable Wall Wash

ELK3322

Finishes:

(W)



#### Sq. Adjustable Baffle

ELK3393

Finishes:

(W)



#### Sq. Adjustable Pinhole

ELK3327

Finishes:

(B, BB, BZ)

\*Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring



Must be used  
with Maximum  
Adjustability Housing