ELCO Lighting

Project name:

Fixture type:

Date:

3" LED Light Engine with Baffle Trim

Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 3" Cedar™ System Housings.
- Frosted acrylic module lens for even lumen distribution.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	9.6W
Lumens	850 lm
Color Temp.	SunsetK
Lamp Type	LED
Beam Angle	60°
CRI	93+
Damp Location	Listed

Options

All White

Black w/White Trim

All Bronze

All Black

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System housing with compatible lumen rating.

LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant.



© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Product Number Builder Example: **E314C0827W2**

3" Cedar Baffle	Lumen	Color Temp	Finish	Generation	Beam Angle
E314C					
	08 850 lm **10** 1000 lm	**27** 2700K **30** 3000K **35** 3500K **40** 4000K **50** 5000K **SD** Sunset [1]	**W** All White **B** Black with White Trim **BZ** All Bronze **BB** All Black	**2** Gen 2 **1** Gen 1	60º lens **-F** 38º lens **-N** 24º lens **-S** 15º lens

[1] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **3″ Cedar™ Light Engines**

ELCO Lighting

3″ Cedar™ Dedicated LED ICA Housings

2-Hour Fire Rated
3″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E3FH	Up to 850lm



3″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E3LC	Up to 850lm



3″ ICA Housing
Remodel

CAT NO.	SPECIFICATIONS
E3LRC	Up to 850lm

3″ Cedar™ Dedicated LED Non-IC Housings



3″ Non-IC Housing
New Construction

CAT NO.	SPECIFICATIONS
E3LC	Up to 1000lm



3″ Non-IC Housing
Remodel

CAT NO.	SPECIFICATIONS
E3LRC	Up to 1000lm

PRODUCT NUMBER BUILDER

Housing Type		Lumen		ICA Airtight		Dimming		Optional	
E3FH	Fire Rated	**08**	850 lm	**(Blank)**	Non-IC	**(Blank)**	120V Triac/ELV	**EM1**	Emergency Backup up to 700 lm output
E3LC	New Construction	**10**	1000 lm	**ICA**	IC Airtight	**D**	120/277V Triac/ELV/0-10V	**EM2**	Emergency Backup up to 1100 lm output
E3LRC	Remodel					**L**	Lutron		

© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.