

4" LED Bi-Pin Low Voltage Retrofit Insert Baffle with 5- CCT Switch



Features

- Perfect for retrofitting Low Voltage Housings to LED.
- GU5.3 socket for MR16 retrofit.
- Baffle reduces stray light.
- Flicker free dimming.

Specifications

Wattage	9W
Lumens	600 lm
Voltage	12V AC
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Wet Location	Listed

Dimensions



Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish. Diecast trim ring for durability and lasting quality. Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4" Low Voltage IC and Non-IC versions with GU5.3 base.

Dimmability: Dimmability depends on transformer compatibility (magnetic or electronic).

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EL140CT5W	LED	600 lm	2700K, 3000K, 3500K, 4000K, 5000K	9W	12V AC	Triac/ELV	All White

Product Number Builder Example: EL140CT5W

4" LED Bi-Pin Retrofit Insert

Color Temp.

Finish

EL140

CT5 2700K - 5000K

W All White