

4" LED Light Engine with

Drop Glass Reflector Trim

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 4" Cedar™ System Housings.
- Frosted acrylic module lens for even lumen distribution.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2.  
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

|               |         |
|---------------|---------|
| Wattage       | 18W     |
| Lumens        | 1600 lm |
| Color Temp.   | 5000K   |
| Lamp Type     | LED     |
| Beam Angle    | 60°     |
| CRI           | 93+     |
| Damp Location | Listed  |

Options



Black w/White Trim



All Bronze



Chrome w/White Trim



Chrome w/Nickel Trim



Haze w/White Trim



All White



All Black

Technical Details

**Optics:** Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Trim Construction:** Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

**Installation:** Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaine of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

**Sunset:** Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

**Listings:** cUL Listed for Wet Location. RoHS Compliant.

Dimensions



Product Number Builder




Example: E412C0827W2

|                              |            |                        |                          |            |             |
|------------------------------|------------|------------------------|--------------------------|------------|-------------|
| ELCO 4" Drop Glass Reflector | Lumens     | Color Temp.            | Finish                   | Generation | Beam Angle  |
| E412C                        |            |                        |                          |            |             |
|                              | 08 850 lm  | 27 2700K               | W All White              | 2 Gen 2    | 60° lens    |
|                              | 12 1250 lm | 30 3000K               | BB All Black             | 1 Gen 1    | -F 38° lens |
|                              | 16 1600 lm | 35 3500K               | BZ All Bronze            |            | -N 24° lens |
|                              |            | 40 4000K               | B Black with White Trim  |            | -S 15° lens |
|                              |            | 50 5000K               | C Chrome with White Trim |            |             |
|                              |            | SD Sunset <sup>1</sup> | H Haze with White Trim   |            |             |


<sup>1</sup> Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

For use with 4" Cedar™ Light Engines

4" Cedar™ Dedicated LED ICA Housings


|  |  |  |  |         |                |         |                |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------|----------------|---------|----------------|
| 2-Hour Fire Rated<br>4" ICA Housing<br>New Construction                           | 4" ICA Housing<br>New Construction                                                | 4" ICA Housing<br>New Construction                                                 | 4" ICA Housing<br>Remodel                                                           |         |                |         |                |
| CAT NO.                                                                           | SPECIFICATIONS                                                                    | CAT NO.                                                                            | SPECIFICATIONS                                                                      | CAT NO. | SPECIFICATIONS | CAT NO. | SPECIFICATIONS |
| E4FH                                                                              | Up to 850 lm                                                                      | E4LC                                                                               | Up to 1600 lm                                                                       | E4LC    | Up to 850 lm   | E4LRC   | Up to 850 lm   |

4" Cedar™ Dedicated LED Non-IC Housings




4" Non-IC Housing  
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E4LC    | Up to 1600 lm  |



4" Non-IC Housing  
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E4LC    | Up to 1250 lm  |



4" Non-IC Housing  
Remodel

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E4LRC   | Up to 1250 lm  |

| PRODUCT NUMBER BUILDER |                        |             |                  |                 |                            |
|------------------------|------------------------|-------------|------------------|-----------------|----------------------------|
| Housing Type           |                        | Lumen       |                  | Optional        | Dimming                    |
| <div></div>            |                        | <div></div> |                  | <div></div>     | <div></div>                |
| E4FH                   | Fire Rated (up to 850) | 08          | 850 lm (8.76W)   | (Blank) Non-IC  | (Blank) 120V Triac/ELV     |
| E4LC                   | New Construction       | 12          | 1250 lm (12.88W) | ICA IC Airtight | D 120/277V Triac/ELV/0-10V |
| E4LRC                  | Remodel                | 16          | 1600 lm (18W)    |                 | SD Sunset                  |
|                        |                        |             |                  |                 | L Lutron                   |