ELCO Lighting

Project name:

Fixture type:

Date:

4" LED Light Engine with Wall Wash Reflector Trim

The perfect lighting solution for high-end residential and light commercial projects.

Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 4" Cedar™ System Housings.
- Frosted acrylic module lens for even lumen distribution.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	12.88W
Lumens	1250 lm
Color Temp.	SunsetK
Lamp Type	LED
Beam Angle	60°
CRI	93+
Damp Location	Listed

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant.

Options

All White

All Bronze

Haze w/ White Ring

Chrome w/ White Ring

Black w/ White Ring

All Black

Dimensions



© ELCO Lighting 2026. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Product Number Builder Example: **E411C0827W2**

ELCO 4" Wall Wash	Lumens	Color Temp.	Finish	Generation	Beam Angle
E411C					
	08 850 lm	**27** 2700K	**W** All White	**2** Gen 2	60º lens
	12 1250 lm	**30** 3000K	**BZ** All Bronze	**1** Gen 1	**-F** 38º lens
	16 1600 lm	**35** 3500K	**H** Haze with White Trim		**-N** 24º lens
		40 4000K	**C** Chrome with White Trim		**-S** 15º lens
		50 5000K	**B** Black with White Trim		
		SD Sunset [1]	**BB** All Black		

[1] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

© ELCO Lighting 2026. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Cedar™ Light Engines**

4″ Cedar™ Dedicated LED ICA Housings



2-Hour Fire Rated
4″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E4FH	Up to 850 lm



4″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E4LC	Up to 1600 lm



4″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E4LC	Up to 850 lm



4″ ICA Housing
Remodel

CAT NO.	SPECIFICATIONS
E4LRC	Up to 850 lm

4″ Cedar™ Dedicated LED Non-IC Housings



4″ Non-IC Housing
New Construction

CAT NO.	SPECIFICATIONS
E4LC	Up to 1600 lm



4″ Non-IC Housing
New Construction

CAT NO.	SPECIFICATIONS
E4LC	Up to 1250 lm



4″ Non-IC Housing
Remodel

CAT NO.	SPECIFICATIONS
E4LRC	Up to 1250 lm

PRODUCT NUMBER BUILDER

Housing Type		Lumen		Optional		Dimming	
E4FH	Fire Rated (up to 850)	**08**	850 lm (8.76W)	**(Blank)**	Non-IC	**(Blank)**	120V Triac/ELV
E4LC	New Construction	**12**	1250 lm (12.88W)	**ICA**	IC Airtight	**D**	120/277V Triac/ELV/0-10V
E4LRC	Remodel	**16**	1600 lm (18W)			**SD**	Sunset
						L	Lutron

© ELCO Lighting 2026. All rights reserved • Rev. 25 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.