

4" Phenolic Step Baffle Trim



Features

- Phenolic Step, Metal Ring.
- Lamp: 40W A19 or R16, 50W PAR20 or R20
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



All White



Black w/White Trim



All Bronze



All Nickel



All Black



Nickel w/White Trim



Black w/Nickel Trim



Nickel w/Black Trim



White w/Nickel Trim



Black w/Bronze Trim



Bronze w/White Trim



White w/Bronze Trim

Product Number

Item	Finish
EL993N	All Nickel

4" Phenolic Baffle Metal Trim

Finish

EL993	
	W All White B Black with White Trim N All Nickel BB All Black BZ All Bronze BN Black with Nickel Trim NB Nickel with Black Trim WN White with Nickel Trim NW Nickel with White Trim BBZ Black with Bronze Trim BZW Bronze with White Trim WBZ White with Bronze Trim

Compatible Products

For use with 4" Trims for PAR Lamps



4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing
New Construction


CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L