

4" Reflector Trim with Socket Bracket



Features

- Reflector Trim.
- Integral Socket Bracket to control lamp height.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 5"

Technical Details

- Construction:** Meticulously manufactured trim with a powder coated or anodized finish.
- Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.
- Compatible Housing:** Compatible with 4"Line Voltage IC and Non-IC versions.
- Lamp:** Compatible with Medium base (E26) PAR type.

Options



All White




Chrome w/White
Trim



Chrome w/Bronze
Trim

Dimensions



Product Numbers

Item	Finish
EL999KW	All White
EL999KC	Chrome with White Trim
EL999KCBZ	Chrome with Bronze Trim

4" Reflector Trim

Finish

EL999K

- W** All White
- C** Chrome with White Trim
- CBZ** Chrome with Bronze Trim

Compatible Products

For use with 4" Trims for PAR Lamps



4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing
New Construction


CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L