ELCO Lighting

Project name:

Fixture type:

Date:

4" Square Wall Wash Reflector LED Light Engine Trims

Features

- Light Engines feature premium LED COB.
- Strong and smooth lumen output.
- Color temperatures from 2700K to 5000K or Sunset Dimming option.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	18W
Lumens	1600 lm
Color Temp.	3500K
Lamp Type	LED
CRI	93+
Wet Location	Listed

Technical Details

Optics: Glass lens diffuses light evenly throughout while reducing glare with LED technology.

Reflector Construction: Reflector is one piece, deep, self-flanged construction spun from .05” thick High Grade Aluminum. Reflector allows for minimal glare and a strong glare cut-off.

Installation: Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel and as a Retrofit Kit.

LED Technology:

- Extremely accurate Color Rendering Index of 93+ CRI.
- Efficacy of >90 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cULus Listed for Wet Location. RoHS Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Finish
E442L1635W2	LED	1600 lm	3500K	18W	All White

© ELCO Lighting 2026. All rights reserved • Rev. 26 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Product Number Builder Example: **E442L0827W2**

ELCO 4″ Square Wall Wash Reflector	Lumens	Color Temp.	Finish	Generation	Beam Angle
E442L					
	08 850 lm	**27** 2700K (Up to 3000 lm) [1]	**W** All White	**2** Gen 2	60º lens
	12 1250 lm	**30** 3000K	**H** Haze with White Ring	**1** Gen 1	**-F** 38º lens [1]
	16 1600 lm	**35** 3500K			**-N** 24º lens [1]
	20 2000 lm	**40** 4000K			**-S** 15º lens [1]
	30 3000 lm	**50** 5000K			
	40 4000 lm	**SD** Sunset [1, 2]			

[1] Available for lumen packages up to 3000 lm only

[2] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

© ELCO Lighting 2026. All rights reserved • Rev. 26 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4" Laurel™ Square Light Engines**

4" Laurel™ Commercial Square LED Frames



E4SQLH
4" Square Architectural Frame
* Hanger bars ordered separately



E4SQLF
4" Square Plaster Frame

PRODUCT NUMBER BUILDER

Frame Type	Voltage	Lumen	Dimming	Optional	Generation
E4SQLH Architectural	**U** 120/277V	**08** 850 lm	**D** 0-10/Triac/ELV	**EM1** Emergency Backup up to 700 lm output	**(Blank)** Gen 1
E4SQLF Plaster		**12** 1250 lm		**EM2** Emergency Backup up to 1100 lm output	**2** Gen 2
		16 1600 lm			
		20 2000 lm			
		30 3000 lm			
		40 4000 lm			

© ELCO Lighting 2026. All rights reserved • Rev. 26 Feb 2025 • ELCO Lighting reserves the right to make specification and design changes without notice.