

6" Die-cast Round Baffle Trim for PAR LAMPS

6" diecast round baffle trim. For use with PAR Lamps.



Features

- One-piece diecast 6" Round Baffle trim.
- Lamp: PAR20 or R20

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Torsion springs securely mount trim into the housing and keep ring flush with the ceiling.

Compatible Housing: Compatible with 6" IC and non-IC housings.


Lamp: PAR Lamp

Options



White Bronze

Dimensions



Product Numbers

Item	Finish
ELL6813W	All White
ELL6813BZ	All Bronze

Product Number Builder Example: ELL6813W

6" Round Baffle Trim

Finish

ELL6813


W All White
BZ All Bronze

Compatible Products

For use with **6" Trims for PAR Lamps**




6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket




6" Airtight IC Housing
Double Wall New Construction

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.




6" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7FICA	90W




6" Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.




6" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.



6" Airtight IC Universal Housing
New Construction

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.



6" Airtight IC Universal Housing
Remodel


CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.

6" Accessories




Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L