

6" LED Light Engine with Adjustable Reflector Trim

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	20.6W
Lumens	2000 lm
Color Temp.	5000K
Lamp Type	LED
Beam Angle	60°
CRI	93+
Damp Location	Listed

Options



All White



All Bronze



Black w/White Trim

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System frame with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant. California Title 24 (JA8-2016-E).

Dimensions



Product Number Builder

Example: E617C0827W2

ELCO 6" Adjustable Reflector	Lumens	Color Temp.	Finish	Generation	Beam Angle
E617C					
	08 850 lm	27 2700K	W All White	2 Gen 2	60° lens
	12 1250 lm	30 3000K	BZ All Bronze	1 Gen 1	-F 38° lens
	16 1600 lm	35 3500K	B Black with White Trim		-N 24° lens
	20 2000 lm	40 4000K			-S 15° lens
		50 5000K			
		SD Sunset ¹			

¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

For use with 6" Cedar™ Light Engines

6" Cedar™ Dedicated LED ICA Housings




2-Hour Fire Rated
6" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E6FH	Up to 1250lm




6" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E6LC	Up to 2000lm



6" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E6LC	Up to 1250lm



6" ICA Housing
Remodel

CAT NO.	SPECIFICATIONS
E6LRC	Up to 1250lm

6" Cedar™ Dedicated LED Non-IC Housings

A technical line drawing of a 6-inch non-IC housing for new construction. It shows a cylindrical housing with a mounting bracket on the side and a cable entry point at the bottom.

6" Non-IC Housing
New Construction

A technical line drawing of a 6-inch non-IC housing for remodel. It shows a cylindrical housing with a mounting bracket on the side and a cable entry point at the bottom, similar to the new construction version but with a different mounting bracket.

6" Non-IC Housing
Remodel

CAT NO.

SPECIFICATIONS

E6LC

Up to 2000lm

CAT NO.

SPECIFICATIONS

E6LRC

Up to 2000lm

PRODUCT NUMBER BUILDER					
Housing Type		Lumen	ICA Airtight	Dimming	Optional
E6FH	Fire Rated	08 850 lm	(Blank) Non-IC	(Blank) 120V Triac/ELV	EM1 Emergency Backup up to 700 lm output
E6LC	New Construction	12 1250 lm	ICA IC Airtight	D 120/277V Triac/ELV/0-10V	EM2 Emergency Backup up to 1100 lm output
E6LRC	Remodel	16 1600 lm		L Lutron	
		20 2000 lm			