

6" LED Light Engine with Adjustable Trim (4000-6000 lm)




Features

- USA Designed and Assembled.
- Frame sold separately (see Compatible Housings).
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	36.8W
Lumens	4000 lm
Voltage	
Color Temp.	4000K
Dimmable	
Lamp Type	LED
Beam Angle	60°
CRI	93+
Wet Location	Listed

Options



Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED technology.

Reflector Construction: Reflector is one piece, deep, self-flanged construction spun from .05" thick High Grade Aluminum. Integral gimbal ring has adjustability up to $\pm 25^\circ$ ideal for sloped ceilings and wall wash applications.

Installation: Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel and as a Retrofit Kit.

LED Technology:


- Extremely accurate Color Rendering Index of 93+ CRI.
- Efficacy of >90 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Listings:

- cULus Listed for Wet Location.
- RoHS Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Dimensions



Product Number Builder

Example: E618L0827W2

ELCO 6" Adjustable	Laurel	Lumens	Color Temp.	Finish	Generation
E618	L				
		40 4000 lm 60 6000 lm	30 3000K 35 3500K 40 4000K 50 5000K	W All White B All Black C All Chrome H All Haze HW Haze w/White Ring	Gen 1 2 Gen 2

Compatible Products

For use with 6" Laurel™ Light Engines



6" Laurel™ Commercial LED Frames



6" Architectural Frame
E6LH



6" Plaster Frame
E6LF



6" Remodel Frame
E6LR



6" Retrofit Kit
E6LT

PRODUCT NUMBER BUILDER

Frame Type		Voltage	Lumen	Dimming	Optional	Generation
E6LH	Architectural	U 120/277V	08 850 lm	D Triac/ELV/0-10V	EM1 Emergency Backup up to 700 lm output	(blank) Gen 1
E6LF	Plaster		12 1250 lm	S Sunset	EM2 Emergency Backup up to 1100 lm output	2 Gen 2
E6LR	Remodel		16 1600 lm	L Lutron		
E6LT	Retrofit		20 2000 lm			
			30 3000 lm			
			40 4000 lm			
			60 6000 lm			

PHOTOMETRIC REPORT

Product #: E618L6040H
Wattage/Lumens: 70.3W/ 5668 Lm
Luminaire LPW: 81 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	5534
5	5468
15	4935
25	4019
35	2330
45	476
55	69
65	23
75	8
85	1
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	346	5.2'
6'	154	7.9'
8'	86.5	10.5'
10'	55.3	13.1'

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30°	3733.68	65.90
0-40°	5157.83	91.00
0-60°	5634.92	99.40
0-90°	5668.25	100.00