

6" LED Light Engine with Baffle Trim

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

Wattage	8.76W
Lumens	850 lm
Color Temp.	3000K
Lamp Type	LED
Beam Angle	60°
CRI	93+
Wet Location	Listed

Options



All White

Black w/White ring

All Bronze

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

Installation: Must be installed on a Cedar™ System frame with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.


LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixelation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant. California Title 24 (JA8-2016-E).

Dimensions



Product Number Builder

Example: E614C0827W2

ELCO 6" Baffle	Lumens	Color Temp.	Finish	Generation	Beam Angle
E614C					
	08 850 lm	27 2700K	W All White	2 Gen 2	60º lens
	12 1250 lm	30 3000K	B Black with White Trim	1 Gen 1	-F 38º lens
	16 1600 lm	35 3500K	BZ All Bronze		-N 24º lens
	20 2000 lm	40 4000K	BB All Black		-S 15º lens
		50 5000K			
		SD Sunset ¹			


¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

LED Light Engine

Multiplier: 2700K (x 0.88), 3000K (x 0.92), 3500K (x 0.96)

PHOTOMETRIC REPORT

Product #: E614C2040
Wattage/Lumens: 21.6W/ 1873 Lm
Luminaire LPW: 87 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	2356
5	2304
15	1867
25	1498
35	638
45	58
55	2
65	1
75	0
85	0
90	0

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	147	4.5'
6'	65.4	6.8'
8'	36.8	9.1'
10'	23.6	11.3'

ZONAL LUMEN SUMMARY



Zone	Lumens	% Luminaire
0-30°	1404.49	75.00
0-40°	1806.64	96.50
0-60°	1871.47	99.90
0-90°	1872.88	100.00

Compatible Products


For use with 6" Cedar™ Light Engines




6" Cedar™ Dedicated LED ICA Housings

							
2-Hour Fire Rated 6" ICA Housing New Construction	6" ICA Housing New Construction	6" ICA Housing New Construction	6" ICA Housing Remodel				
CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
E6FH	Up to 1250lm	E6LC	Up to 2000lm	E6LC	Up to 1250lm	E6LRC	Up to 1250lm

6" Cedar™ Dedicated LED Non-IC Housings

A technical line drawing of a 6-inch non-IC housing for new construction. It shows a circular ceiling-mounted fixture with a central light source and a mounting bracket with two screws for installation.

6" Non-IC Housing
New Construction

A technical line drawing of a 6-inch non-IC housing for remodel. It shows a circular ceiling-mounted fixture with a central light source and a mounting bracket with two screws for installation.

6" Non-IC Housing
Remodel

CAT NO.	SPECIFICATIONS
---------	----------------

E6LC	Up to 2000lm
------	--------------

CAT NO.	SPECIFICATIONS
---------	----------------

E6LRC	Up to 2000lm
-------	--------------

PRODUCT NUMBER BUILDER					
Housing Type		Lumen	ICA Airtight	Dimming	Optional
E6FH	Fire Rated	08 850 lm	(Blank) Non-IC	(Blank) 120V Triac/ELV	EM1 Emergency Backup up to 700 lm output
E6LC	New Construction	12 1250 lm	ICA IC Airtight	D 120/277V Triac/ELV/0-10V	EM2 Emergency Backup up to 1100 lm output
E6LRC	Remodel	16 1600 lm		L Lutron	
		20 2000 lm			