ELCO Lighting

Project name:

Fixture type:

Date:

# 6" LED Light Engine with Drop Glass Trim

The perfect lighting solution for high-end residential and light commercial projects.

## Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.

## Specifications

| | |
|---|---|
| **Wattage** | 12.88W |
| **Lumens** | 1250 lm |
| **Color Temp.** | 2700K |
| **Lamp Type** | LED |
| **Beam Angle** | 60° |
| **CRI** | 93+ |
| **Damp Location** | Listed |

## Technical Details

**Optics**: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Trim Construction**: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.

**Installation:** Must be installed on a Cedar™ System frame with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

**LED Technology:** Extremely accurate Color Rendering Index of 93+. Efficacy of 97 lumens per watt. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing ELCO Red heat sink. Instant On to Full Brightness technology. No LED pixelation.

**Sunset:** Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

**Listings**: cUL Listed, Wet Location. RoHS Compliant. California Title 24 (JA8-2016-E).

## Options

**All White**

**Haze w/White Trim**

**Gold w/White Trim**

**Chrome w/White Trim**

**All Bronze**

**Black w/White Trim**

## Dimensions





© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Product Number Builder Example: **E612C0827W2**

| ELCO 6" Drop Glass | Lumens | Color Temp. | Finish | Generation | Beam Angle |
|---|---|---|---|---|---|
| **E612C** | | | | | |
| | **08** 850 lm | **27** 2700K | **W** All White | **2** Gen 2 | 60º lens |
| | **12** 1250 lm | **30** 3000K | **BZ** All Bronze | **1** Gen 1 | **-F** 38º lens |
| | **16** 1600 lm | **35** 3500K | **B** Black with White Trim | | **-N** 24º lens |
| | **20** 2000 lm | **40** 4000K | **C** Chrome with White Trim | | **-S** 15º lens |
| | | **50** 5000K | **H** Haze with White Trim | | |
| | | **SD** Sunset [1] | **G** Gold with White Trim | | |

[1] Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

## LED Light Engine

Multiplier: 2700K (x 0.96), 3500K (x 1.04), 4000K (x 1.08)

### PHOTOMETRIC REPORT

Product #: E612C1230
Wattage/Lumens: 15.7W/ 1076 Lm
Luminaire LPW: 69 Lm/W




### CANDLE POWER SUMMARY

| Degrees Vertical | 0° |
|---|---|
| 0 | 1715 |
| 5 | 1614 |
| 15 | 1099 |
| 25 | 864 |
| 35 | 322 |
| 45 | 24 |
| 55 | 1 |
| 65 | 1 |
| 75 | 0 |
| 85 | 0 |
| 90 | 0 |

### ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Footcandles Beam Center | Beam Diameter |
|---|---|---|
| 4' | 107 | 3.8' |
| 6' | 47.6 | 5.6' |
| 8' | 26.8 | 7.5' |
| 10' | 17.1 | 9.4' |

### ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|---|---|---|
| 0-30° | 839.73 | 78.00 |
| 0-40° | 1048.35 | 97.40 |
| 0-60° | 1075.43 | 99.90 |
| 0-90° | 1076.31 | 100.00 |

## LED Light Engine

Multiplier: 2700K (x 0.96), 3500 (x 1.04), 4000K (x 1.08)

### PHOTOMETRIC REPORT

Product #: E612C2030
Wattage/Lumens: 21.6W/ 1751 Lm
Luminaire LPW: 81 Lm/W




### CANDLE POWER SUMMARY

| Degrees Vertical | 0° |
|---|---|
| 0 | 2203 |
| 5 | 2155 |
| 15 | 1746 |
| 25 | 1401 |
| 35 | 597 |
| 45 | 55 |
| 55 | 2 |
| 65 | 1 |
| 75 | 0 |
| 85 | 0 |
| 90 | 0 |

### ILLUMINANCE AT A DISTANCE

| Distance to Target Plane | Footcandles Beam Center | Beam Diameter |
|---|---|---|
| 4' | 138 | 4.5' |
| 6' | 61.2 | 6.8' |
| 8' | 34.4 | 9.1' |
| 10' | 22.0 | 11.3' |

### ZONAL LUMEN SUMMARY

| Zone | Lumens | % Luminaire |
|---|---|---|
| 0-30° | 1313.28 | 75.00 |
| 0-40° | 1689.32 | 96.50 |
| 0-60° | 1749.93 | 99.90 |
| 0-90° | 1751.25 | 100.00 |


© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Compatible Products

For use with **6″ Cedar™ Light Engines**

## 6″ Cedar™ Dedicated LED ICA Housings

2-Hour Fire Rated
6″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6FH | Up to 1250lm |

6″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6LC | Up to 2000lm |



6″ ICA Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6LC | Up to 1250lm |



6″ ICA Housing
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6LRC | Up to 1250lm |

## 6″ Cedar™ Dedicated LED Non-IC Housings



6″ Non-IC Housing
**New Construction**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6LC | Up to 2000lm |



6″ Non-IC Housing
**Remodel**

| CAT NO. | SPECIFICATIONS |
|---|---|
| E6LRC | Up to 2000lm |

### PRODUCT NUMBER BUILDER

| Housing Type | Lumen | ICA Airtight | Dimming | Optional |
|---|---|---|---|---|
| **E6FH** Fire Rated | **08** 850 lm | **(Blank)** Non-IC | **(Blank)** 120V Triac/ELV | **EM1** Emergency Backup up to 700 lm output |
| **E6LC** New Construction | **12** 1250 lm | **ICA** IC Airtight | **D** 120/277V Triac/ELV/0-10V | **EM2** Emergency Backup up to 1100 lm output |
| **E6LRC** Remodel | **16** 1600 lm | | **L** Lutron | |
| | **20** 2000 lm | | | |

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2026. All rights reserved • Rev. 19 Mar 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.