

6" Ply Sylo™ Pendant

This unique Ply Sylo™ LED Pendant gives you the options you are looking for. Engineered with energy-efficient LED technology and dimming options for your project.




Features

- Modern Pendant Die-Cast aluminum fixture for easy maintenance and upgrades
- Integral EM option 15W Max, for over 15W use EJB4ICA-EM5 external EM and housing
- Available with 120" Field Cuttable Cable or Stems (12", 24", 36", 48", 60", 72" and 84")
- Fits 3 ½" and 4" Octagon and Round Junction boxes
- Manual switch to choose desired Color Temperature and Lumen Output
- 120V Triac/ELV dimming or 120/277V 0-10V dimming options available
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- 90+ CRI for extremely accurate color rendering
- CA Title 24, ETL listed, ENERGY STAR, JA8-2022-E
- Life span of 50,000 hours L70

Specifications

Wattage	14, 18, 24W
Lumens	1000, 1500, 2000 lm
Voltage	120/277V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	0-10V
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



Technical Details

- Optics:** Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.
- Construction:** Integrated driver and light engine with quick connect. Diecast aluminum body with heat sink allows for efficient cooling. High quality powder coat finish preventing rust and paint cracking.
- Installation:** Included bracket mounts to 3 ½" and 4" Octagon and Round Junction boxes.
- Electrical:** Specifiable in 120V or 120/277V input . High Efficiency driver with a power factor > 0.9. Start time of less than .75 seconds.
- Emergency Battery Backup:** Integral EM Test Switch on Cylinder. The fixture becomes 120V only. Integral EM option 15W Max, for over 15W use EJB4ICA-EM5 external EM and housing


LED Technology: Extremely accurate Color Rendering Index of 90+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

Dimmability: Optional Triac/ELV or 0-10V dimming. For full list of dimmers, refer to the Dimmer Compatibility List. Industry-leading dimming that dims smoothly with no hot spots or flickering.

Listings: cUL Listed for Wet Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2019 standards.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EPD685L3CT5BB	LED	1000, 1500, 2000 lm	2700K, 3000K, 3500K, 4000K, 5000K	14, 18, 24	120/277V	0-10V	All Black

6" Ply Sylo™ Pendant	Dimming	Lumen Output (Wattage)	Color Temp.	Color Finish	Length	Optional
EPD6						
	37 120V, Triac/ELV ¹ 85 120/277V, 0-10V ²	L3 1000/1500/2000(14/18/24W) _{3, 4} 10 1000 lumen (15W) ^{5, 6}	CT5 2700K-5000K ⁷	W All White BB All Black ⁸ HW White with Haze Reflector	120" Cable Mount ⁹ -12 12" Stem ¹⁰ -24 24" Stem ¹⁰ -36 36" Stem ¹⁰ -48 48" Stem ¹⁰ -60 60" Stem ¹⁰ -72 72" Stem ¹⁰ -84 84" Stem ¹⁰	No Emergency Battery EM Em. battery 15W MAX. ¹¹

¹ Available as 120V, Triac/ELV
² Available as 120/277V, 0-10V/Triac/ELV
³ Manual lumen switch located on module
⁴ Lumen Switch: 1000/1500/2000 lm
⁵ Available as 120V, Triac/ELV
⁶ Available in All White (W) and White/Haze (HW) only
⁷ Manual CCT switch located on module
⁸ All Black (BB) only available in L3 only
⁹ 120" field cuttable cable
¹⁰ Stem is not field cuttable
¹¹ Fixture becomes 120V only