

6" Reflector Baffle Trim



Features

- Reflector with Baffle.
- Lamp: (1) 42W max CFL, 75W MAX PAR30, 100W MAX A19.
- O.D.: 7 1/4".

Technical Details

- Construction:**
- Meticulously manufactured trim with a powder coated or anodized finish.
 - Baffle helps reduce glare.
- Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.
- Compatible Housing:** Compatible with 6" Integrated LED Housings.
- Lamp:** Compatible with Medium base (E26) PAR type.

Options



Black w/White Trim



All Bronze



All White

Product Numbers

Item	Finish
ELA101B	Black with White Trim
ELA101BZ	All Bronze
ELA101W	All White

Product Number Builder Example: ELA101B

6" Reflector with Baffle Trim

ELA101

Finish


- B** Black with White Trim
BZ All Bronze
W All White

Compatible Products

For use with **6" Trims for PAR Lamps**




6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket



6" Airtight IC Housing
Double Wall New Construction

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.




6" Airtight IC 2-Hour Fire Rated Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7FICA	90W




6" Airtight IC Housing
Remodel

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.




6" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.



6" Airtight IC Universal Housing
New Construction

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.



6" Airtight IC Universal Housing
Remodel


CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.

6" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L