

6" Shower Trim with Albalite Lens



Features

- Shower Trim.
- Lamp: 42W MAX. 4 Pin CFL, 60W MAX A19.
- 8" O.D.

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated Line Voltage Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Options



White



Black



Bronze



Lexan

Product Numbers

Item	Finish
EL12W	All White
EL12B	All Black
EL12BZ	All Bronze
EL12SH	Lexan Ring
EL12KSH	White Lexan

Product Number Builder Example: EL12W

6" Shower Trim

Socket Bracket

Finish

EL12

no Socket Bracket

K Socket Bracket

W All White

B All Black

BZ All Bronze


SH Lexan

Compatible Products


For use with **6" Trims for PAR Lamps**



6" Line Voltage ICA Housings



6" Airtight IC Housing
New Construction



6" Airtight IC Housing
Double Wall New Construction




6" Airtight IC 2-Hour Fire Rated Housing
New Construction


CAT NO.	SPECIFICATIONS
EL7ICA	90W, with Socket Bracket
EL7ICANB	90W, without Socket Bracket

CAT NO.	SPECIFICATIONS
EL7IC100A	Lamp: 100W MAX.


CAT NO.	SPECIFICATIONS
EL7FICA	90W



6" Airtight IC Housing
Remodel



6" Airtight IC Housing with GU24 Base Socket
New Construction




6" Airtight IC Universal Housing
New Construction

CAT NO.	SPECIFICATIONS
EL7RICA	Lamp: 90W MAX.

CAT NO.	SPECIFICATIONS
EL7ICA-G24	Lamp: 27W MAX.

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.




6" Airtight IC Universal Housing
Remodel

CAT NO.	SPECIFICATIONS
RR10H	Lamp: 150W MAX.


6" Accessories



Fire Cover



Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L