

8" Wall Wash LED Light

Engine Trims (4000-6000 lm)



Features	Specifications														
- Dimmable Triac/ELV or 0-10V. - USA Designed and Assembled. - Frame sold separately (see Compatible Housings). 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.	<table> <tr> <td>Wattage</td><td>36.8W</td></tr> <tr> <td>Lumens</td><td>4000 lm</td></tr> <tr> <td>Color Temp.</td><td>4000K</td></tr> <tr> <td>Lamp Type</td><td>LED</td></tr> <tr> <td>Beam Angle</td><td>60°</td></tr> <tr> <td>CRI</td><td>93+</td></tr> <tr> <td>Wet Location</td><td>Listed</td></tr> </table>	Wattage	36.8W	Lumens	4000 lm	Color Temp.	4000K	Lamp Type	LED	Beam Angle	60°	CRI	93+	Wet Location	Listed
Wattage	36.8W														
Lumens	4000 lm														
Color Temp.	4000K														
Lamp Type	LED														
Beam Angle	60°														
CRI	93+														
Wet Location	Listed														

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED technology.


Reflector Construction: Reflector is one piece, deep, self-flanged construction spun from .05” thick High Grade Aluminum. Reflector allows for minimal glare and a strong glare cut-off. Wall wash reflector pushes light in one direction to evenly light up a wall or frame.

Installation: Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel and as a Retrofit Kit.


- LED Technology:**
 - Extremely accurate Color Rendering Index of 93+ CRI.
 - Efficacy of >90 lumens per watt.
 - Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
 - Superior Thermal Management by utilizing ELCO Red heat sink.
 - Instant On to Full Brightness technology.
 - No LED pixilation.

Listings:
 - cULus Listed for Wet Location.
 - RoHS Compliant.

Warranty: ELCO Products are built to last. 5-year Limited warranty.



Dimensions



Product Number Builder

Example: E811L4030W2

ELCO 8" Wall Wash	Laurel	Lumens	Color Temp.	Finish	Generation
E811	L				
		40 4000 lm 60 6000 lm	30 3000K 35 3500K 40 4000K 50 5000K	H All Haze W All White B All Black C All Chrome HW Haze w/White Ring	Gen 1 2 Gen 2

Compatible Products

For use with 8" Laurel™ Light Engines



8" Laurel™ Commercial LED Frames



8" Architectural Frame
E8LH



8" Plaster Frame
E8LF



8" Remodel Frame
E8LR



8" Retrofit Kit
E8LT

PRODUCT NUMBER BUILDER

Frame Type	Voltage	Lumen	Dimming	Optional	Generation
E8LH Architectural	U 120/277V	08 850 lm	D Triac/ELV/0-10V	EM1 Emergency Backup up to 700 lm output	(blank) Gen 1
E8LF Plaster		12 1250 lm	S Sunset	EM2 Emergency Backup up to 1100 lm output	2 Gen 2
E8LR Remodel		16 1600 lm	L Lutron		
E8LT Retrofit		20 2000 lm			
		30 3000 lm			
		40 4000 lm			
		60 6000 lm			