

Koto™ Architectural LED Light Engine

Works with 2", 3", 4" & 6" Koto™ Architectural Recessed Housings and Koto™ Trims




Features

- Light engine used with Koto™ Architectural Housings
- See Koto™ Architectural housings for lumen output options. Final lumen output is determined by housing.
- Driver on housing extends lifespan and allows for more dimming and EM options
- Standard 38° Lens installed, 25° and 60° lens included with each module - Optional Lens: 18° (EP731C)
- Optional: Louver (L45), Linear Lens (L46), Spread Lens (L47), Frosted Lens (L49),
- Optional Reflectors: 15° (EP735C), 25° (EP736C), 38° (EP737C), 60° (EP738C)
- Works in 2", 3", 4" & 6" ELCO Housings with Koto™ twist-on trims
- Excellent color rendering 95+ CRI
- Sunset option dims from 3000K to 1800K
- ENERGY STAR Certified
- Title 24 JA8-2019 Compliant
- Life span of 50,000 hours L70
- Covered by U.S. PATENTS and Patents Pending

Specifications

Wattage	18.9 MAX.W
Lumens	1360 MAX. lm
Color Temp.	2700K
Lamp Type	LED
Beam Angle	38°
CRI	95
Wet Location	cUL Listed w/Wet Location Trim
Damp Location	cUL Listed

Dimensions



Technical Details

Optics: PC lens diffuses light evenly throughout while reducing glare with LED COB technology.

Construction: Diecast aluminum body with heat fins allow for efficient cooling.

Compatible Housings: Koto™ Module is compatible with Architectural Housings:

- 120V/277V 0-10V/Triac/ELV (3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%)
- 120V Triac/ELV with optional Emergency Battery Backup.

• E2LK57RICAD, E3LK65ICA, E3LK66ICAD, E3LK65RICA, E3LK66RICAD, E4LK87ICA, E4LK88ICAD, E4LK87RICA, E4LK88RICAD, ELK72FICA, ELK73FICAD (10W, 250mA) **ELK19 Delivered Lumens:** 2700K: 750 lm, 3000K: 770 lm, 3500K: 790 lm, 4000K: 810 lm, Sunset: 750 lm **ELK21 Delivered Lumens:** 2700K: 890 lm, 3000K: 930 lm, 3500K: 990 lm, 4000K: 1020 lm **ELK24 Delivered Lumens:** 2700K: 1016 lm, 3000K: 1060 lm, 3500K: 1100 lm, 4000K: 1150 lm

• E2LK34ICA, E2LK35ICAD, E3LK76ICA, E3LK77ICAD, E4LK98ICA, E4LK99ICAD (15W, 350mA) **ELK19 Delivered Lumens:** 2700K: 970 lm, 3000K: 1000 lm, 3500K: 1030 lm, 4000K: 1050 lm, Sunset: 940 lm **ELK21 Delivered Lumens:** 2700K: 1140 lm, 3000K: 1200 lm, 3500K: 1270 lm, 4000K: 1390 lm **ELK24 Delivered Lumens:** 2700K: 1390 lm, 3000K: 1450 lm, 3500K: 1510 lm, 4000K: 1570 lm

• E2LK41ICA, E2LK42ICAD, E3LK53ICA, E3LK54ICAD, E4LK47ICA, E4LK48ICAD (17W, 400mA) **ELK21 Delivered Lumens:** 2700K: 1220 lm, 3000K: 1290 lm, 3500K: 1360 lm, 4000K: 1400 lm **ELK24 Delivered Lumens:** 2700K: 1550 lm, 3000K: 1620 lm, 3500K: 1685 lm, 4000K: 1750 lm

• E2LK94ICA, E2LK95ICAD, E3LK84ICA, E3LK85ICAD, E4LK78ICA, E4LK79ICAD, E6LK56ICA, E6LK57ICAD (19W, 450mA) **ELK21 Delivered Lumens:** 2700K: 1360 lm, 3000K: 1430 lm, 3500K: 1510 lm, 4000K: 1690 lm

Product Number

Item	Lamp type	Lumens	CCT	Watts	Beam Angle
ELK2127D	LED	1360 MAX. lm	2700K	18.9 MAX.	38°

Compatible Architectural Housings - LUMEN OUTPUT per module					
Architectural Koto™ LED Module	Standard Housings (10W)	Shallow Housings (15W)	High Lumen Housings (17W)	High Lumen Housings (19W)	2-Hr Fire Rated Housings
	E2LK5 Series, E3LK6 Series, E4LK8 Series, E6LK37 Series*	E2LK3 Series, E3LK7 Series, E4LK9 Series	E2LK4 Series, E3LK5 Series, E4LK4 Series	E2LK9 Series, E3LK8 Series, E4LK7 Series, E6LK5 Series	ELK7 Series, ELK9 Series
ELK19 Series	~750 lm	~1000 lm	Not Compatible	Not Compatible	~750 lm
ELK21 Series	~950 lm	~1200 lm	~1450 lm	~1650 lm	~950 lm
ELK24 Series	~1100 lm	~1400 lm	~1750 lm	~1950 lm	~1100 lm

* For ELK21 & ELK24 Series Only

Installation: Twist-on design for toolless trim installation, for use with Koto™ trims only. Can be use in 2", 3" & 4" Architectural Koto™ Housings only.

LED Technology: Extremely accurate Color Rendering Index (CRI) of 95+. Lumen Maintaince of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness. No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Dimmability: Based on housing used. See Koto™ Architectural Housings for options.

Listings: cUL Listed for Damp Locations. cUL Listed for Wet Location with Wet location trims. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2019.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Number Builder Example: ELK1927D

Koto™ Architectural LED Module	Lumens (Wattage)	Color Temp.	Beam Angle
ELK			
	19 Up to 1050 lm (14.7W MAX) ¹	27D 2700K	38º ⁴
	21 Up to 1690 lm (18.9W MAX) ¹	30D 3000K	-S 18º
	24 Up to 1950 lm (18.9W MAX) ¹	35D 3500K	-N 25º
		40D 4000K	-W 60º
		SD Sunset (ELK19 Only) ^{2, 3}	-E 90º ⁵

¹ Lumen output varies based on the architectural Koto housing used

² Available with ELK19 module only

³ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

⁴ 38° lens installed. Includes 25° and 60° lens with module.


⁵ 90° Frosted Reflector

Compatible Products

For use with **Koto™ Architectural LED Light Engine**




2" Koto™ Architectural Recessed Housings




2" Shallow Maximum Adjustability ICA Housing
1000 lm (14.7W) w/ELK19 Series Module
1200 lm (14.7W) w/ELK21 Series Module
1500 lm (14.7W) w/ELK24 Series Module
Shallow New Construction

CAT NO.	SPECIFICATIONS
E2LK34ICA	120V - Triac/ELV
E2LK35ICAD	120/277V - 0-10V/Triac/ELV ¹



2" Maximum Adjustability ICA Housing
1350 lm (15.7W) w/ELK21 Series Module
1650 lm (15.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E2LK41ICA	120V - Triac/ELV
E2LK42ICAD	120/27V - 0-10V/Triac/ELV ¹



2" Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
1850 lm (18.9W) w/ELK24 Series Module
High Lumen New Construction

CAT NO.	SPECIFICATIONS
E2LK94ICA	120V - Triac/ELV
E2LK95ICAD	120/27V - 0-10V/Triac/ELV ¹

¹ 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

2" Pex™ Twist-On Trims



Round Deep Reflector
ELK2818
Finishes:
(W, B, H, BB, BZ)




Round Adjustable Reflector
ELK2829
Finishes:
(W, B, H, BB, BZ)




Round Adjustable Pinhole
ELK2827
Finishes:
(W, B, BB, BZ)




Round Curved Reflector
ELK2872
Finishes:
(W, B*)



Square Deep Reflector
ELK2518
Finishes:
(W, B, BB)



Square Adjustable Reflector
ELK2529
Finishes:
(W, B, BB)



Square Reflector
ELK2541
Finishes:
(W, B, BB)



Square Adjustable Pinhole
ELK2527
Finishes:
(W, B, BB)



Round Gimbal
ELK2888
Finishes:
(W, B*, BZ)



Square Gimbal
ELK2588
Finishes:
(W, B*, BZ)



Round Adj. Trimless Reflector
ELK215
Finishes:
(W, B*)



Trimless Spackle Frame
EL25FR
For use with ELK215

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK2872, ELK2888, ELK2588, & ELK215)

Compatible Products

For use with **Koto™ Architectural LED Light Engine**



3" Koto™ Architectural Recessed Housings



3" High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
1650-1850 lm (18.9W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK53ICA	120V - Triac/ELV
E3LK54ICAD	120/277V - 0-10V/Triac/ELV ¹
E3LK84ICA	120V - Triac/ELV
E3LK85ICAD	120/277V - 0-10V/Triac/ELV ¹



3" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
1500 lm (14.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV ¹



3" Standard ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	Emergency Battery Back-Up
E3LK66ICAD	120/277V - 0-10V/Triac/ELV ¹
E3LK66ICAD-EM1	Emergency Battery Back-Up



3" Standard ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
Remodel

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV
E3LK66RICAD	120/277V - 0-10V/Triac/ELV ¹




2-Hour Fire Rated 3" ICA Housing
750 lm (10.5W) w/ELK19 Series Module
950 lm (10.5W) w/ELK21 Series Module
1350 lm (10.5W) w/ELK24 Series Module
New Construction


CAT NO.	SPECIFICATIONS
ELK72FICA	120V - Triac/ELV
ELK73FICAD	120/277V - 0-10V/Triac/ELV ¹

¹ 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

3" Pex™ Twist-On Trims



Round Deep Reflector
ELK3618
Finishes:
(W, BB, BZ, B, C, H)



Round Adjustable Gimbal
ELK3629
Finishes:
(W, BB, BZ, B, C, H)




Round Adjustable Pinhole
ELK3627
Finishes:
(B, BB, BZ, B, H)




Round Adj. Slot Aperture
ELK3620
Finishes:
(W)




Round Adj. Wall Wash
ELK3622
Finishes:
(W)



Round Regressed Eyeball
ELK3653
Finishes:
(W, BB, B)



Round Curved Reflector
ELK3672
Finishes:
(W, B)



Round Directional Gimbal
ELK3679
Finishes:
(W, BB, B, H)


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK3672)

Compatible Products

For use with **Koto™** Architectural LED Light Engine




3" Pex™ Twist-On Trims



Round Adjustable Baffle

ELK3693


Finishes:
(W)



Square Deep Reflector

ELK3318


Finishes:
(W, BB, BZ, B, C, H)



Square Adjustable Reflector

ELK3329

Finishes:
(W, BB, BZ, B, C, H)



Square Adj. Wall Wash

ELK3322


Finishes:
(W)



Square Adjustable Pinhole

ELK3327


Finishes:
(W, BB, BZ, B, H)



Square Reflector

ELK3341

Finishes:
(W, BB, BZ, B)




Square Adjustable Baffle

ELK3393

Finishes:
(W)


3" Pex™ Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL3FMR

Compatible 3" Pex™ Round trims:
ELK3618, ELK3629, ELK3627, ELK3693,
ELK3620, ELK3622 Series




Square Flush Mount Trim Adaptor

EL3FMS

Compatible 3" Pex™ Square trims:
ELK3318, ELK3329, ELK3322, ELK3327,
ELK3341, ELK3393 Series

3" Pex™ Trimless



Round Trimless

Reflector

ELK308

Finishes:
(W, B, H)



Round Adjustable

Trimless Reflector

ELK315

Finishes:
(W, B, H)



Round Trimless

Spackle Frame

EL3SFR

For use with ELK315



Round Knife Edge Wood
Ceiling Trim w/Mounting Clips

EL3WCR

Finishes:
(W, B)



Square Trimless

Reflector

ELK370

Finishes:
(W, B, H)



Square Adjustable

Trimless Reflector

ELK381

Finishes:
(W, B, H)



Square Trimless

Spackle Frame

EL03SFS

For use with ELK370 & ELK381

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK315, ELK370, & ELK381)

Compatible Products

For use with **Koto™ Architectural LED Light Engine**



4" Koto™ Architectural Recessed Housings




4" High Lumen Maximum Adjustability ICA Housing
1500 lm (15.7W) w/ELK21 Series Module
1650-1850 lm (15.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK47ICA	120V - Triac/ELV
E4LK48ICAD	120/277V - 0-10V/Triac/ELV ¹
E4LK78ICA	120V - Triac/ELV
E4LK79ICAD	120/277V - 0-10V/Triac/ELV ¹



4" Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
1500 lm (14.7W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V - Triac/ELV
E4LK99ICAD	120/277V - 0-10V/Triac/ELV ¹



4" Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
1350 lm (11.8W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK87ICA	120V - Triac/ELV
E4LK87ICA-EM1	Emergency Battery Back-Up
E4LK88ICAD	120/277V - 0-10V/Triac/ELV ¹
E4LK88ICAD-EM1	Emergency Battery Back-Up



4" Standard ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
1350 lm (11.8W) w/ELK24 Series Module
Remodel

CAT NO.	SPECIFICATIONS
E4LK87RICA	120V - Triac/ELV
E4LK88RICAD	120/277V - 0-10V/Triac/ELV ¹




2-Hour Fire Rated 4" ICA Housing
750 lm (11.8W) w/ELK19 Series Module
950 lm (11.8W) w/ELK21 Series Module
1100 lm (11.8W) w/ELK24 Series Module
New Construction

CAT NO.	SPECIFICATIONS
ELK93FICA	120V - Triac/ELV
ELK94FICAD	120/277V - 0-10V/Triac/ELV ¹



4" ICA Housing for 2-Hr Fire Rated Ceilings
New Construction
Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716

CAT NO.	SPECIFICATIONS
E4JB85ICA	120V - Triac/ELV
E4JB85ICA-EM1	Emergency Battery Back-Up
E4JB86ICAD	120/277V - 0-10V/Triac/ELV ¹
E4JB86ICAD-EM1	Emergency Battery Back-Up



4" ICA Housing for 2-Hr Fire Rated Ceilings
Remodel
Compatible Trims: ELK4116, ELK4127, ELK4129, ELK4188, ELK4710, ELK4713, ELK4715, ELK4216, ELK4229, ELK4227, ELK4714, & ELK4716

CAT NO.	SPECIFICATIONS
E4JB85RICA	120V - Triac/ELV
E4JB85RICA-EM1	Emergency Battery Back-Up
E4JB86RICAD	120/277V - 0-10V/Triac/ELV ¹
E4JB86RICAD-EM1	Emergency Battery Back-Up


¹ 3 in 1 dimming: Triac, ELV and 0-10V dimming in one driver to 1%

Compatible Products

For use with **Koto™** Architectural LED Light Engine

EL ELCO Lighting

4" Pex™ Twist-On Trims



Shallow Reflector
ELK4116
Finishes:
(W, H)



Deep Reflector
ELK4118
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector
ELK4129
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector with Clear Glass
ELK4111
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector with Frosted Lens
ELK4112
Finishes:
(W, BB, BZ, B, C, H)



Rotatable Slot Aperture
ELK4120
Finishes:
(W)



Adjustable Wall Wash
ELK4122
Finishes:
(W)



Adjustable Pinhole
ELK4127
Finishes:
(W, BB, BZ, B, H)



Adjustable Pinhole with Frosted Glass
ELK4125
Finishes:
(W, BB, BZ, B, H)



Slot Aperture
ELK4130
Finishes:
(W)



Adjustable Spot
ELK4188
Finishes:
(W, B, BZ)




Regressed Eyeball
ELK4153
Finishes:
(W, BB, B)



Curved Reflector
ELK4172
Finishes:
(W, B)



Directional Gimbal
ELK4179
Finishes:
(W, BB, B, H)



Adjustable Baffle
ELK4193
Finishes:
(W, BB, B)




Shallow Reflector
ELK4216
Finishes:
(W, H)



Deep Reflector
ELK4218
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Gimbal
ELK4229
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Slot Rotatable Aperture
ELK4220
Finishes:
(W)



Adjustable Wall Wash
ELK4222
Finishes:
(W)



Adjustable Pinhole
ELK4227
Finishes:
(W, BB, BZ, B, C, H)



Adjustable Reflector
ELK4282
Finishes:
(W, BZ)



Adjustable Baffle
ELK4284
Finishes:
(W, B, BZ)



Adj. Phenolic Baffle
ELK4293
Finishes:
(W, BB, B)

4" Pex™ Flush Mount Trim Adaptors



Round Flush Mount Trim Adaptor

EL4FMR

Compatible 3" Pex™ Round trims:
ELK4116, ELK4118, ELK4127, ELK4129,
ELK4710, ELK4713, ELK4715 Series



Square Flush Mount Trim Adaptor

EL4FMS

Compatible 3" Pex™ Square trims:
ELK4216, ELK4218, ELK4227,
ELK4229 Series

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK4188, ELK4172, & ELK4284)

Compatible Products

For use with **Koto™ Architectural LED Light Engine**

EL ELCO Lighting

4" Pex™ Trimless



Round Trimless Reflector

ELK408
Finishes:
(W, B, H, BZ)




Round Adj. Trimless Reflector

ELK415
Finishes:
(W, B, H, BZ)




Round Trimless Spackle Frame

EL4SFR
For use with ELK408 & ELK415




Smooth Reflector

ELK430
Finishes:
(W, B, BZ)




Baffle

ELK434
Finishes:
(W, B, BZ)




Square Trimless Reflector

ELK445
Finishes:
(W, B, H)



Square Trimless Adj. Reflector

ELK459
Finishes:
(W, B, H)



Square Trimless Spackle Frame

EL4SFS
For use with ELK445 & ELK459

Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK408, ELK415, ELK434, ELK445, ELK459)

4" Flexa™ Twist-On Trims



Round Reflector

ELK4721
Finishes:
(WW, BB, BZBZ, BW, CW, HW)




Round Baffle

ELK4723
Finishes:
(WW, BB, BZBZ, BW)




Square Reflector

ELK4741
Finishes:
(WW, BB, BZBZ, BW, HW)
**Not for Remodel Housing*



Square Baffle

ELK4743
Finishes:
(WW, BB, BZBZ, BW)
**Not for Remodel Housing*



Square Adj. Reflector


ELK4759
Finishes:
(WW, BB, B, H)
**Not for Remodel Housing*

4" Unique™ Twist-On Trims



Round Adjustable Reflector

ELK4710
Finishes:
(W, B, BZ)



Round Adjustable Baffle

ELK4713
Finishes:
(W, BZ)




Round Wall Wash

ELK4715
Finishes:
(W, BZ)



Round Adj. Deep Reflector

ELK4717
Finishes:
(W, BZ)




Round Adj. Deep Baffle

ELK4719
Finishes:
(W)



Square Reflector

ELK4714
Finishes:
(W, B, BZ)
**Not for Remodel Housing*



Square Baffle

ELK4716
Finishes:
(W, BZ)
**Not for Remodel Housing*


*Finishes: **W** - All White, **WW** - All White, **B** - Black Reflector w/White Ring, **C** - Chrome Reflector w/White Ring, **H** - Haze Reflector w/White Ring, **BB** - All Black, **BZ** - All Bronze, **CC** - All Chrome, **BZBZ** - All Bronze, **BW** - Black Reflector w/White Ring, **CW** - Chrome Reflector w/White Ring, **CN** - Chrome Reflector w/Nickel Ring, **HW** - Haze Reflector w/White Ring

Compatible Products




For use with **Koto™ Architectural LED Light Engine**

6" Koto™ Architectural Recessed Housings



6" High Lumen Maximum Adjustability ICA Housing
1250 lm (15.9W) w/ELK21 Series Module
1650-1800 lm (18.9W) w/ELK24 Series Module

New Construction



6" Standard ICA Housing
1100 lm (14.7W) w/ELK21 Series Module
1500 lm (14.7W) w/ELK24 Series Module

New Construction

CAT NO.	SPECIFICATIONS
E6LK43ICA	120V - Triac/ELV
E6LK44ICAD	120/277V - 0-10V/Triac/ELV ¹
E6LK56ICA	120V - Triac/ELV
E6LK57ICAD	120/277V - 0-10V/Triac/ELV ¹


CAT NO.	SPECIFICATIONS
E6LK37ICA	120V - Triac/ELV
E6LK37ICA-EM1	Emergency Battery Back-Up
E6LK38ICAD	120/277V - 0-10V/Triac/ELV ¹
E6LK38ICAD-EM1	Emergency Battery Back-Up

5" & 6" Pex™ Twist-On Trims



5" Round Reflector

ELK5421
Finishes:
(W)




5" Round Baffle

ELK5493
Finishes:
(W)



6" Round Reflector

ELK6418
Finishes:
(W, BB, BZ, H)



6" Round Adj. Reflector

ELK6429
Finishes:
(W, BB, BZ, H)




6" Round Adj. Slot Aperture

ELK6420W
Finishes:
(W)



6" Round Adj. Pinhole Reflector

ELK6427
Finishes:
(W, B, H)



6" Square Adj. Reflector

ELK6829
Finishes:
(W, BB, H)

6" Flexa™ Twist-On Trims




6" Round Reflector

ELK610
Finishes:
(WW, BB, BZBZ, CC, BW, CW, HW)



6" Round Adjustable Reflector

ELK629
Finishes:
(WW, BB, BZBZ, BW, CW, HW)




6" Round Adjustable Baffle

ELK693
Finishes:
(WW, BB, BZBZ, BW)



6" Round Reflector

ELK6710
Finishes:
(W, B, BZ)



6" Round Baffle

ELK6713
Finishes:
(W, BZ)



6" Round Wall Wash

ELK6715
Finishes:
(W, BZ)

6" Unique™ Twist-On Trims


Finishes: **W** - All White, **BB** - All Black, **BZ** - All Bronze, **B** - Black w/White Ring, **C** - Chrome w/White Ring, **H** - Haze w/White Ring, **B*** - All Black (For ELK6710, ELK6713, ELK6715)

Photometric Report

Koto™ Architectural LED Module

PHOTOMETRIC REPORT

Product #: ELK2127D
Wattage / Lumens: 12.22W / 1169.3 lm
Luminaire LPW: 95.7 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1829
5	1737
15	1353
25	683
35	328
45	123
55	39
65	17
75	8
85	2
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	114	3.0'
6'	50.8	4.6'
8'	28.6	6.1'
10'	18.3	7.6'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	834.5	71.2
0-40°	1,022.9	87.3
0-60°	1,140.0	97.3
0-90°	1,164.3	99.4

PHOTOMETRIC REPORT

Product #: ELK2130D
Wattage / Lumens: 12.22W / 1218 lm
Luminaire LPW: 99.6 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1900
5	1805
15	1406
25	710
35	341
45	127
55	41
65	17
75	9
85	2
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	119	3.0'
6'	52.8	4.6'
8'	29.7	6.1'
10'	19.0	7.6'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	867.0	71.2
0-40°	1,062.8	87.3
0-60°	1,184.4	97.3
0-90°	1,209.7	99.4

PHOTOMETRIC REPORT

Product #: ELK2135D
Wattage / Lumens: 12.22W / 1271 lm
Luminaire LPW: 104 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	1976
5	1877
15	1462
25	738
35	355
45	133
55	43
65	18
75	9
85	2
90	1

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	124	3.0'
6'	54.9	4.6'
8'	30.9	6.1'
10'	19.8	7.6'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	901.7	71.2
0-40°	1,105.3	87.3
0-60°	1,231.8	97.3
0-90°	1,258.1	99.4

PHOTOMETRIC REPORT

Product #: ELK2140D
Wattage / Lumens: 12.22W / 1322 lm
Luminaire LPW: 108.2 lm/W



CANDLE POWER SUMMARY

Degress Vertical	0°
0	2051
5	1948
15	1518
25	766
35	368
45	138
55	44
65	19
75	9
85	2
90	1

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	128	3.0'
6'	57.0	4.6'
8'	32.1	6.1'
10'	20.5	7.6'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	935.9	71.2
0-40°	1,147.2	87.3
0-60°	1,278.5	97.3
0-90°	1,305.8	99.4

Photometric Report

Koto™ Architectural LED Module

PHOTOMETRIC REPORT

Product #: ELK2130D-W (E4LK79ICAD)
Wattage / Lumens: 17.9W / 1584.3 lm
Luminaire LPW: 88.5 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	1880
5	1753
15	1396
25	892
35	399
45	170
55	50
65	21
75	11
85	6
90	5

ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	118	3.9'
6'	52.2	5.9'
8'	29.4	7.9'
10'	18.8	9.8'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	1,042.6	65.8
0-40°	1,346.3	85
0-60°	1,545.5	97.6
0-90°	1,584.0	100

PHOTOMETRIC REPORT

Product #: ELK2135D-W (E4LK79ICAD)
Wattage / Lumens: 17.9W / 1647.3 lm
Luminaire LPW: 92 lm/W



CANDLE POWER SUMMARY

Degree Vertical	0°
0	1955
5	1824
15	1452
25	928
35	415
45	177
55	52
65	21
75	11
85	6
90	5

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	122	3.9'
6'	54.3	5.9'
8'	30.6	7.9'
10'	19.6	9.8'

ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	1,084.3	65.8
0-40°	1,400.1	85
0-60°	1,607.3	97.6
0-90°	1,647.4	100