

LED Bait™ Die-Cast Aluminum Pendants



Features

- 2" x 8" Pendant.
- Diecast aluminum housing.
- Standard 38° lens included, EP719C - 15°, EP720 - 25° available.
- Dimmable.
- Canopy included.
- 3/8" OD steel stem (sold separately).
- Snoot & Louver available (sold separately).
- ETL Listed

Specifications

Wattage	10W
Lumens	700 lm
Voltage	120V
Color Temp.	3000K, 3500K, 4000KK
Dimmable	Triac
Lamp Type	LED

Options



White



Black




Optional Snoot

Beam Angle 38°
Damp Location Listed



Optional Louver

Dimensions



Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
EDL80CT3B	LED	700 lm	3000K, 3500K, 4000KK	10W	120V	Triac	38°	All Black

Product Number Builder Example: EDL8030W

ELCO 2" x 8" Pendant

EDL

Size

80 2 x 8

Color Temp

30 3000K
CT3 3000K, 3500K, 4000K

Finish

W All White
B All Black



ELCO Lighting

Dimmer Compatibility Chart LED Diecast Aluminum Pendants

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Ariadni®/Toggler® C·L Single Pole/3-Way Dimmer	AYCL-153P	10% - 100%
	Ariadni®/Toggler® C·L Single Pole/3-Way Dimmer	AYCL-233P	10% - 100%
	Skylark Contour® C·L, Single Pole/3-Way Dimmer	CTCL-153P	10% - 100%
	Diva® (gloss) C·L Single Pole/3-Way Dimmer	DVCL-153P	5% - 86%
	Diva® (gloss) C·L Single Pole/3-Way Dimmer	DVCL-253P	5% - 86%
	Diva® (gloss) Single Pole, Electronic Low Voltage Dimmer	DVELV-300P	10% - 100%
	Diva® (gloss) 3-Way, Magnetic Low Voltage Dimmer	DVLV-603P	10% - 100%
	Diva® (satin) C·L Single Pole/3-Way Dimmer	DVSCCL-153P	10% - 100%
	Diva® (satin) C·L Single Pole/3-Way Dimmer	DVSCCL-253P	10% - 100%
	Grafik® T C·L, Single Pole Dimmer	GT-150	10% - 100%
	Grafick® T Wireless C·L, Single Pole or Multi-Location Dimmer	GTJ-250M	5% - 80%
	Skylark® C·L Single Pole/3-Way Dimmer	SCL-153P	10% - 100%
	Skylark® Single Pole, Electronic Low Voltage, Preset Dimmer	SELV-300P	10% - 100%
	Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer	TGCL-153P	5% - 86%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.