

Lotus™ LED Undercabinet Light



Features

- Slim LED Undercabinet Light with mini linking connector included for row mounting, linkable end-to-end.
- Solid aluminum construction with white polycarbonate lens.
- Knockout on back and bottom for easy access to wiring compartment, hardwire installation or plug and play.
- ON/OFF switch, individually switched with pass-through power.
- Captive screws for easy mounting.
- Lamp: LED CREE array chip.
- LED Driver: 120V AC, dimmable (included).
- CA Title 24 compliant (JA8-2016).
- cUL Listed.
- Life span of 35,000 hours L70

Specifications

Wattage	19.5W
Lumens	1450 lm
Voltage	120V
Color Temp.	4000K
Dimmable	Triac/ELV
Lamp Type	LED


Options



Bronze

White

Dimension



Product Number

Item	Description	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EUB48L40BZ	48" Length	LED	1450 lm	4000K	19.5W	120V	Triac/ELV	All Bronze

Compatible Products

Lotus™ LED Undercabinet Light



Accessories




Linking Connectors

CAT NO.	SPECIFICATIONS
EUBC03	3" Length
EUBC06	6" Length
EUBC012	12" Length
EUBC024	24" Length



5' Power Cord

CAT NO.	SPECIFICATIONS
EUBCRD	5' Length



J-Box for Hard Wire Supply Connection

CAT NO.	SPECIFICATIONS
EUBJBX	White
EUBJBXBZ	Bronze



ELCO Lighting

Dimmer Compatibility Chart

Lotus™ LED Undercabinet Lights

For EUB11, EUB12, EUB14, EUB18, EUB22, EUB29, EUB32, EUB36, EUB42, and EUB48 Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Skylark Contour, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way Indoor Application, Residential/Commercial Application	CT-603PG / CT-600PR	10% - 100%
	Diva, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential/Commercial Application	DV-600PR / DV603PG	10% - 100%
	Diva, 120V, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	DVW-603PGH / DVCL-153P	10% - 100%
	Maestro, 120V, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	MACL-153M / TGCL-153P	10% - 100%
	Skylark, Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer	S-600PR / S-2-LH	10% - 100%
Leviton		1A1505 / IC1605	10% - 100%
	SureSlide, 120V AC 60Hz, 600W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing	6631 / 6633	10% - 100%
Cooper	Decorator Dimmer, 120V 60Hz, 300W for LED and CFL, 600W for Incandescent, Single Pole, 3-Way, Polycarbonated Housing	DLC03P	10% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com