

# New Construction Multiple Frame for Oak™ Recessed



## Features

- E1LF1
- New Construction Multiple Frame for downlight E1L02, E1L12 & E111F, and E1AK02 &E1AK12.
  - IC Rated with E1L02 and E1L12.
  - For row mounting fixtures.
  - Requires transformer

- E1LF2
- New Construction Multiple Frame for adjustable E1L32 & E1L22, and E1AK22 & E1AK32
  - IC Rated with E1L32, E1L22 series
  - Requires Transformer.
  - For row mounting fixtures.

## Technical Details

- Spacing:
- E1LF1-M2, E1LF2-M2: Minimum spacing required between the first and last frames is 8 3/4".
  - E1LF1-M3, E1LF2-M3: Minimum spacing required between the first and last frames is 13".
  - E1LF1-M4, E1LF2-M4: Minimum spacing required between the first and last frames is 17 1/2".
  - E1LF1-M5, E1LF2-M5: Minimum spacing required between the first and last frames is 21 3/4".

## Options



E1LF1-M2



E1LF2-M2

## E1LF1-M



## E1LF2-M



## Product Number

| Item     | Description                                           |
|----------|-------------------------------------------------------|
| E1LF1-M2 | 2 sets for Downlight (Total length of frames: 8 3/4") |

# Compatible Products



For use with 1" Oak™ IC Rated Frames

## 1" Oak™ Recessed Downlight LED Light Engines - use with E1LF1



**E1L02 Series**  
**Round Downlight**  
Finishes:  
(W, B, BZ, H, BB)



**E1L12 Series**  
**Square Downlight**  
Finishes:  
(W, B, BZ, H, BB)




**E111**  
**Cove Light**  
Finishes:  
(W)

## 1" Oak™ Recessed Adjustable LED Light Engines - use with E1LF2



**E1L32 Series**  
**Round Gimbal**  
Finishes:  
(W, B, BZ)



**E1L22 Series**  
**Square Pull Down**  
Finishes:  
(W, B, BZ)

### PRODUCT NUMBER BUILDER

| Oak™ Light Engine | Style               | Beam Angle |                | Color Temperature |       | Finish |                   |
|-------------------|---------------------|------------|----------------|-------------------|-------|--------|-------------------|
| E1L               |                     |            |                |                   |       |        |                   |
|                   | 02 Round Downlight  | F          | 38° (Standard) | 27                | 2700K | W      | All White         |
|                   | 12 Square Downlight | NF         | 28°            | 30                | 3000K | B      | Black             |
|                   | 32 Round Gimbal     | WF         | 60°            | 35                | 3500K | BZ     | All Bronze        |
|                   | 22 Square Pull Down |            |                | 40                | 4000K | H      | Haze w/White Ring |
|                   |                     |            |                |                   |       | BB     | All Black         |

# Compatible Products

For use with 1" Oak™ Rated Frames




## 1" Oak™ 12V AC Transformers




**Enclosed Electronic Transformer**

| CAT NO.  | SPECIFICATIONS |
|----------|----------------|
| E1LDRV60 | ELV Dimmable   |



**Electronic Transformer**

| CAT NO.    | SPECIFICATIONS    |
|------------|-------------------|
| LET-60     | 120V Input        |
| LET-60H    | 120V Input, Hatch |
| LET-60-277 | 277V Input        |



**0-10V Dimmable Electronic Transformer**

| CAT NO.      | SPECIFICATIONS |
|--------------|----------------|
| LET-60DX     | 120V Input     |
| LET-60DX-277 | 277V Input     |



**Magnetic Transformer**


| CAT NO.  | SPECIFICATIONS       |
|----------|----------------------|
| ETR12    | 50W, Daisy Chain 2-6 |
| ETR12-20 | 20W, Daisy Chain 1-3 |

## 1" Oak™ Accessories



Downlight Trims  
For E1L02 & E1L12

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| RM1W    | All White           |
| RM1B    | Black w/ White Ring |
| RM1BZ   | All Bronze          |
| RM1H    | Haze w/ White Ring  |
| RM1BB   | All Black           |



Downlight Trims  
For E1L02 & E1L12

| CAT NO. | SPECIFICATIONS      |
|---------|---------------------|
| RM11W   | All White           |
| RM11B   | Black w/ White Ring |
| RM11BZ  | All Bronze          |
| RM11H   | Haze w/ White Ring  |
| RM11BB  | All Black           |



Optional Lenses for  
E1L02, E1L12, & E1L32

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| EP713C  | 28°            |
| EP715C  | 50°            |