

Oak™ Housings with 12V AC Transformer





Features

- R60 Insulation housing, IC Airtight
- Includes individual electronic transformer
- 2" cutout for downlight (E1L02, E1L12 and E11F)
- 2 3/8" cutout for adjustable (E1L32 & E2L22)
- 2 1/2" cutout for trimless (EL01SFR + E1L61)
- Suitable for Chicago Plenum construction



Specifications

Voltage	120V or 277V
Dimmable	ELV, 0-10V



E1LF1



E1LF2



E1LF3TL



Product Numbers

Item	Description	Voltage	Dimming
E1LF1ICAJ	For Oak Downlight	120V	ELV
E1LF1ICAJ-7	For Oak Downlight	277V	
E1LF1ICAJDX	For Oak Downlight	120V	0-10V
E1LF1ICAJDX-7	For Oak Downlight	277V	0-10V
E1LF2ICAJ	For Oak Adjustable	120V	ELV
E1LF2ICAJ-7	For Oak Adjustable	277V	
E1LF2ICAJDX	For Oak Adjustable	120V	0-10V
E1LF2ICAJDX-7	For Oak Adjustable	277V	0-10V
E1LF3TLICAJ	For Oak Trimless	120V	ELV
E1LF3TLICAJ-7	For Oak Trimless	277V	
E1LF3TLICAJDX	For Oak Trimless	120V	0-10V
E1LF3TLICAJDX-7	For Oak Trimless	277V	0-10V

Product Number Builder Example: E1LF1ICAJ

Elco Oak™ Mounting Frame

E1LF

Cutout

1 For Oak Downlight

2 For Oak Adjustable

3TL For Oak Trimless

IC Airtight

ICAJ ICA

Dimming

120V Input/ELV Dimmable

-7 277V Input

DX 120V Input/0-10V Dimmable

DX-7 277V Input/0-10V Dimmable

Compatible Products



For use with 1" Oak™ IC Rated R60 Insulation Housing

1" Oak™ Recessed Downlight LED Light Engines - use with E1LF1ICAJ Series



E1L02 Series
Round Downlight
Finishes:
(W, B, BZ, H, BB)




E1L12 Series
Square Downlight
Finishes:
(W, B, BZ, H, BB)




E111
Cove Light
Finishes:
(W)

1" Oak™ Recessed Adjustable LED Light Engines - use with E1LF2ICAJ Series




E1L32 Series
Round Gimbal
Finishes:
(W, B, BZ)



E1L22 Series
Square Pull Down
Finishes:
(W, B, BZ)

1" Oak™ Recessed Trimless LED Light Engines - use with E1LF3TLICAJ Series



E1L61 Series
Round Trimless
Finishes:
(W, B, BZ)

PRODUCT NUMBER BUILDER

Oak™ Light Engine	Style	Beam Angle		Color Temperature		Finish	
E1L							
	02 Round Downlight	F	38° (Standard)	27	2700K	W	All White
	12 Square Downlight	NF	28°	30	3000K	B	Black
	32 Round Gimbal	WF	60°	35	3500K	BZ	All Bronze
	22 Square Pull Down			40	4000K	H	Haze w/White Ring
	61 Round Trimless			SD	Sunset	BB	All Black

Compatible Products

For use with 1" Oak™ IC Rated R60 Insulation Housing




1" Oak™ Accessories



Downlight Trims
For E1L02 & E1L12

CAT NO.	SPECIFICATIONS
RM1W	All White
RM1B	Black w/ White Ring
RM1BZ	All Bronze
RM1H	Haze w/ White Ring
RM1BB	All Black



Downlight Trims
For E1L02 & E1L12

CAT NO.	SPECIFICATIONS
RM11W	All White
RM11B	Black w/ White Ring
RM11BZ	All Bronze
RM11H	Haze w/ White Ring
RM11BB	All Black



Optional Lenses for
E1L02, E1L12, & E1L32

CAT NO.	SPECIFICATIONS
EP713C	28°
EP715C	50°