ELCO Lighting

Project name:

Fixture type:

Date:

Pex™ 3" Square Adjustable Reflector Wall Wash

Pex™ precision die-cast adjustable trims with Twist-On system for easy Koto™ Module installation

Features

- 3″ Square Adjustable Reflector Wall Wash.
- 35° Adjustability
- 4 3/8″ Sq.
- Convenient twist-on design for easy installation.
- Damp Location Rated.
- Lamp: Koto™ LED Module.
- Recommended to be used with Maximum Adjustability Housings

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-on design allows for easy mounting onto the Koto™ LED Module.

Lamp: Koto™ LED Module.

Options

All White

Dimensions





Product Numbers

Item	Finish
ELK3322W	All White

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2026. All rights reserved • Rev. 18 Nov 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Product Number Builder Example: **ELK3322W**

Pex™ 3″ Square Adjustable Reflector Wall Wash	Finish
ELK3322	
	W All White

© ELCO Lighting 2026. All rights reserved • Rev. 18 Nov 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **3″ Koto™ Twist-On Trims**

Koto™ LED Module & 3″ Dedicated LED ICA Housing



Koto™ LED Module
ELK07 - ELK09

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	**27** 2700K	**(blank)** 38° lens (Standard)
	09 950 lm	**30** 3000K	**-S** 18° lens
		35 3500K	**-N** 25° lens
		40 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK09 Only)	



3″ ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability

Koto™ Architectural LED Light Engine & 3″ Architectural ICA Housings



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 750 - 850 lm	**27D** 2700K	**(blank)** 38° lens (Standard)
	21 1100 - 1500 lm	**30D** 3000K	**-S** 18° lens
		35D 3500K	**-N** 25° lens
		40D 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK19 Only)	



3″ High Lumen Maximum Adjustability ICA Housing
1500 lm (18.9W) w/ELK21 Series Module
Not for use with ELK19 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK85ICAD	120/277V - 0-10V/Triac/ELV



3″ Shallow Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV

ACCESSORIES FOR KOTO™ LED MODULE & KOTO™ ARCHITECTURAL LED LIGHT ENGINE

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver	**L51**	Color Shifter
L46	Linear Louver	**L57**	White Hex Louver
L47	Spread Louver	**L52**	Blue Lens
L49	Frosted Lens	**L53**	Pink Shifter

Snoot

L50W	White
L50B	Black

© ELCO Lighting 2026. All rights reserved • Rev. 18 Nov 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **3″ Koto™ Twist-On Trims**

Koto™ 24V DC LED Light Engine



24V DC Koto™ LED Light Engine

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Voltage
ELK			
	08 800 lm	**27** 2700K	**-24** 24V DC
		30 3000K	

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included with standard module*

Snoot

L50W	White
L50B	Black

Secondary Optics

L45	Hex Louver	**L57**	White Hex Louver
L46	Linear Lens	**L52**	Blue Lens
L47	Spread Louver	**L53**	Pink Shifter
L49	Frosted Lens		
L51	Color Shifter		

3″ Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 3″ ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
E24V386ICA	Maximum Adjustability

**Requires 24V DC Transformer*

© ELCO Lighting 2026. All rights reserved • Rev. 18 Nov 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.