ELCO Lighting

Project name:

Fixture type:

Date:

# Pex™ 4" Round Adjustable Wall Wash

Pex™ Precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation

## Features

- 4″ Round Adjustable Reflector Wall Wash
- 45° Adjustability
- 5″ O.D.
- Convenient twist-lock design for easy installation
- Damp Location Rated
- Lamp: Koto™ LED Module
- Recommended to be used with Maximum Adjustability Housings

## Technical Details

**Construction:** Diecast aluminum with a powder coated finish.

**Installation:** Twist-lock design allows for easy mounting onto the Koto™ LED Module.

**Lamp:** Koto™ LED Module.

## Dimensions







## Product Numbers

| Item | Finish |
|---|---|
| **ELK4122W** | All White |

## Product Number Builder

Example: **ELK4122W**

| Pex™ 4″ Round Adjustable Reflector Wall Wash | Finish |
|---|---|
| **ELK4122** | |
| | **W** All White |


© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Compatible Products

For use with **4″ Koto™ Twist-On Trims**

## Koto™ LED Module & 4″ Dedicated LED ICA Housing



Koto™ LED Module
**ELK07, ELK09, & ELK11**



Koto™ LED Module with 5-CCT Switch

**Product Number**

| | |
|---|---|
| **ELK08CT5** | 825 lm, 5-CCT, 120V |
| **ELK10CT5** | 1000 lm, 5-CCT, 120V |

**PRODUCT NUMBER BUILDER**

| Koto™ LED Module | Lumens | | Color Temperature | | Beam Angle | |
|---|---|---|---|---|---|---|
| ELK | | | | | | |
| | **07** | 750 lm | **27** | 2700K | **(blank)** | 38° lens (Standard) |
| | **09** | 950 lm | **30** | 3000K | **-S** | 18° lens |
| | **11** | 1150 lm | **35** | 3500K | **-N** | 25° lens |
| | | | **40** | 4000K | **-W** | 60° lens |
| | | | **SD** | Sunset Dimming (For ELK09 & ELK11) | **-FC** | 18° - 50° Adjustable (ELK07 Only) |

**ACCESSORIES**

**Lens**

| | |
|---|---|
| **EP731C*** | 18° Lens |
| **EP732C*** | 25° Lens |
| **EP733C*** | 38° Lens |
| **EP734C*** | 60° Lens |

**EP732C, EP733C, EP734C Included with standard module*

**Snoot**

| | |
|---|---|
| **L50W** | White |
| **L50B** | Black |

**Secondary Optics**

| | |
|---|---|
| **L45** | Hex Louver |
| **L46** | Linear Lens |
| **L47** | Spread Louver |
| **L49** | Frosted Lens |
| **L51** | Color Shifter |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

## 4″ Koto™ Dedicated LED ICA Housings



4″ ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---|---|
| EL485ICA | Maximum Adjustability |


© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Compatible Products

For use with **4″ Koto™ Twist-On Trims**

## Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
**ELK19 - ELK21**

### PRODUCT NUMBER BUILDER

| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
|---|---|---|---|
| ELK | | | |
| | **19** 750 - 850 lm | **27D** 2700K | **(blank)** 38° lens (Standard) |
| | **21** 1100 - 1500 lm | **30D** 3000K | **-S** 18° lens |
| | | **35D** 3500K | **-N** 25° lens |
| | | **40D** 4000K | **-W** 60° lens |
| | | **SD** Sunset Dimming (ELK19 Only) | **-FC** 18° - 50° Adjustable (ELK21 Only) |

*Standard module includes 38° installed with 25° & 60° field changeable lenses.

### ACCESSORIES

**Lens**

**EP731C** 18° Lens
**EP732C** 25° Lens
**EP733C** 38° Lens
**EP734C** 60° Lens

*EP732C, EP733C, EP734C Included with standard module

**Snoot**

**L50W** White
**L50B** Black

**Secondary Optics**

**L45** Hex Louver
**L46** Linear Lens
**L47** Spread Louver
**L49** Frosted Lens
**L51** Color Shifter

## 4″ Koto™ Architectural Recessed Housings



4″ Maximum Adjustability ICA Housing
*Use with ELK21 Series Module*
*Not for use with ELK19 Series Module*
New Construction

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LK47ICA | 1350 lm, 15.7W, 120V, Triac/ELV |
| E4LK48ICAD | 1350 lm, 15.7W, 120/277V, 0-10V/Triac/ELV |
| E4LK78ICA | 1500 lm, 18.9W, 120V, Triac/ELV |
| E4LK79ICAD | 1500 lm, 18.9W, 120/277V, 0-10V/Triac/ELV |



4″ Shallow Maximum Adjustability ICA Housing
*1000 lm (14.7W) w/ELK19 Series Module*
*1200 lm (14.7W) w/ELK21 Series Module*
New Construction

| CAT NO. | SPECIFICATIONS |
|---|---|
| E4LK98ICA | 120V, Triac/ELV |
| E4LK99ICAD | 120/277V, 0-10V/Triac/ELV |


© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

# Compatible Products

For use with **4″ Koto™ Twist-On Trims**

## Koto™ 24V DC LED Light Engine



24V DC Koto™ LED Light Engine

**PRODUCT NUMBER BUILDER**

| Koto™ LED Light Engine | Lumens | Color Temperature | Voltage |
|---|---|---|---|
| ELK | | | |
| | **08** 800 lm | **27** 2700K | **-24** 24V DC |
| | | **30** 3000K | |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

**ACCESSORIES**

**Lens**

| | |
|---|---|
| **EP731C** | 18° Lens |
| **EP732C** | 25° Lens |
| **EP733C** | 38° Lens |
| **EP734C** | 60° Lens |

**EP732C, EP733C, EP734C Included with standard module*

**Snoot**

| | |
|---|---|
| **L50W** | White |
| **L50B** | Black |

**Secondary Optics**

| | | | |
|---|---|---|---|
| **L45** | Hex Louver | **L57** | White Hex Louver |
| **L46** | Linear Lens | **L52** | Blue Lens |
| **L47** | Spread Louver | **L53** | Pink Shifter |
| **L49** | Frosted Lens | | |
| **L51** | Color Shifter | | |

## 4″ Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 4″ ICA Maximum Adjustability Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---|---|
| E24V485ICA | Maximum Adjustability |

**Requires 24V DC Transformer*


© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.