ELCO Lighting

Project name:

Fixture type:

Date:

Pex™ 4" Round Adjustable Wall Wash

Pex™ Precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation

Features

- 4″ Round Adjustable Reflector Wall Wash
- 45° Adjustability
- 5″ O.D.
- Convenient twist-lock design for easy installation
- Damp Location Rated
- Lamp: Koto™ LED Module
- Recommended to be used with Maximum Adjustability Housings

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module.

Lamp: Koto™ LED Module.

Dimensions





Product Numbers

Item	Finish
ELK4122W	All White

Product Number Builder

Example: **ELK4122W**

Pex™ 4″ Round Adjustable Reflector Wall Wash	Finish
ELK4122	
	W All White

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Koto™ Twist-On Trims**

Koto™ LED Module & 4″ Dedicated LED ICA Housing



Koto™ LED Module
ELK07, ELK09, & ELK11



Koto™ LED Module with 5-CCT Switch

Product Number

ELK08CT5	825 lm, 5-CCT, 120V
ELK10CT5	1000 lm, 5-CCT, 120V

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens		Color Temperature		Beam Angle	
ELK						
	07	750 lm	**27**	2700K	**(blank)**	38° lens (Standard)
	09	950 lm	**30**	3000K	**-S**	18° lens
	11	1150 lm	**35**	3500K	**-N**	25° lens
			40	4000K	**-W**	60° lens
			SD	Sunset Dimming (For ELK09 & ELK11)	**-FC**	18° - 50° Adjustable (ELK07 Only)

ACCESSORIES

Lens

EP731C*	18° Lens
EP732C*	25° Lens
EP733C*	38° Lens
EP734C*	60° Lens

**EP732C, EP733C, EP734C Included with standard module*

Snoot

L50W	White
L50B	Black

Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L51	Color Shifter

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

4″ Koto™ Dedicated LED ICA Housings



4″ ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL485ICA	Maximum Adjustability

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Koto™ Twist-On Trims**

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK			
	19 750 - 850 lm	**27D** 2700K	**(blank)** 38° lens (Standard)
	21 1100 - 1500 lm	**30D** 3000K	**-S** 18° lens
		35D 3500K	**-N** 25° lens
		40D 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK19 Only)	**-FC** 18° - 50° Adjustable (ELK21 Only)

*Standard module includes 38° installed with 25° & 60° field changeable lenses.

ACCESSORIES

Lens

EP731C 18° Lens
EP732C 25° Lens
EP733C 38° Lens
EP734C 60° Lens

*EP732C, EP733C, EP734C Included with standard module

Snoot

L50W White
L50B Black

Secondary Optics

L45 Hex Louver
L46 Linear Lens
L47 Spread Louver
L49 Frosted Lens
L51 Color Shifter

4″ Koto™ Architectural Recessed Housings



4″ Maximum Adjustability ICA Housing
Use with ELK21 Series Module
Not for use with ELK19 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK47ICA	1350 lm, 15.7W, 120V, Triac/ELV
E4LK48ICAD	1350 lm, 15.7W, 120/277V, 0-10V/Triac/ELV
E4LK78ICA	1500 lm, 18.9W, 120V, Triac/ELV
E4LK79ICAD	1500 lm, 18.9W, 120/277V, 0-10V/Triac/ELV



4″ Shallow Maximum Adjustability ICA Housing
1000 lm (14.7W) w/ELK19 Series Module
1200 lm (14.7W) w/ELK21 Series Module
New Construction

CAT NO.	SPECIFICATIONS
E4LK98ICA	120V, Triac/ELV
E4LK99ICAD	120/277V, 0-10V/Triac/ELV

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **4″ Koto™ Twist-On Trims**

Koto™ 24V DC LED Light Engine



24V DC Koto™ LED Light Engine

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Voltage
ELK			
	08 800 lm	**27** 2700K	**-24** 24V DC
		30 3000K	

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included with standard module*

Snoot

L50W	White
L50B	Black

Secondary Optics

L45	Hex Louver	**L57**	White Hex Louver
L46	Linear Lens	**L52**	Blue Lens
L47	Spread Louver	**L53**	Pink Shifter
L49	Frosted Lens		
L51	Color Shifter		

4″ Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 4″ ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
E24V485ICA	Maximum Adjustability

**Requires 24V DC Transformer*

© ELCO Lighting 2026. All rights reserved • Rev. 08 Oct 2024 • ELCO Lighting reserves the right to make specification and design changes without notice.