

Universal Dimmable LED Driver (Small)




Features

- Small universal dimmable LED drivers
- For indoor and outdoor use
- Suitable for damp locations
- Triac/ELV/MLV dimmable
- 120/277V
- ETL listed
- Class II, short circuit and overload protection

Specifications

Wattage	24W - 60W
Voltage	12V DC (2A) or 24V DC (2.5A)
Dimmable	Triac/ELV/MLV

Dimensions



Product Numbers

Item	Watts	Voltage	Dimming
DRVU12V24WD	24W	12V DC (2A)	Triac/ELV/MLV
DRVU12V60WD	60W	12V DC (5A)	Triac/ELV/MLV
DRVU24V24WD	24W	24V DC (1A)	Triac/ELV/MLV
DRVU24V60WD	60W	24V DC (2.5A)	Triac/ELV/MLV



ELCO Lighting

Dimmer Compatibility Chart

Universal Dimmable LED Driver (Small)

For DRVU12V24WD, DRVU12V60WD,
DRVU24V24WD, and DRVU24V60WD

For Reference Only


Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	Toggle, 120V AC, 60Hz, 300W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	TSL06-1LW	10% - 100%
Legrand	120V AC, 60Hz, 450/700W Incandescent, LED/CFL, Single Pole, 3-Way	RHCL-453P	10% - 100%
Lutron	Toggle, 120V AC, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way	TGCL-153P	10% - 100%
	Skylark, 120V AC, 150W CFL/LED, 600W Incandescent, Single Pole, 3-Way	SCL-153P	10% - 100%
	Caseta, 120V AC, 150W CFL/LED, 600W Incandescent, Single Pole, Multi Location	PD-6WCL	10% - 100%
	Diva, 120V AC, 60Hz, 600W Magnetic Low Voltage, Single Pole	DV-600P	10% - 100%
	Diva, 120V AC, 60Hz, 600W Magnetic Low Voltage, Single Pole, Commercial/Residential Application	DVLV-600P	10% - 100%
	Diva, 120V AC, 60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Commercial/Residential, Indoor Application	DVCL-153P	10% - 100%
	Skylark, 120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, Commercial/Residential Application	S-600P	10% - 100%
	Skylark, 120V, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way,	LG-603P	10% - 100%

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com