

4" LAUREL™
DOWNLIGHTING SYSTEM

8.8W-44.1W, 2700K-5000K, or Sunset, Up to 3000 lm,
120V or 120/277V

THE LAUREL™ SYSTEM

A full line of high quality commercial grade LED lighting with different size apertures, lumen outputs, and color temperatures. A great solution for hospitality, retail, and commercial projects



FEATURES

- Design allows for quiet, glare-free ceiling
- Spun extra deep aluminum single piece reflectors
- 55° Cutoff
- Optional 90 minutes, 120/277 VAC, 60Hz Emergency Backup.
- USA designed and assembled.
- 2 at the end of the item number denotes Generation 2. Please note Gen 2 and Gen 1 are not cross compatible.
- Driver on frame/retrofit kit.
- Excellent color rendering 93+ CRI.
- IC rated for direct contact with insulation for 850 lm and 1250 lm packages


SPECIFICATIONS

Wattage	8.8W - 44.1W MAX.
Lumens	850 lm - 3000 lm
Voltage	120/277V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K, Sunset
CRI	93+
Wet Location	Listed
Dimming	Dims down to 1% with Triac/ELV/0-10V Dimmers
Beam Angle	15°, 24°, 38°, 60°

Finishes	White
	Black
	Chrome/ White
	Haze
	Haze/White

SET UP

1. Select a New Construction, Remodel, or Retrofit.
2. Select a Laurel LED Light Engine.



PRODUCT NUMBER BUILDER

STEP 1. Specify Housing part number (Select one) Example: E4LFU08D2

4" IC AIRTIGHT RECESSED HOUSINGS

ITEM	ROUND FRAME	VOLTAGE	LUMENS	DIMMING	OPTIONAL
E4L					
E4L	H Architectural	U 120/227V	08 850 lm	D2 Triac/ELV/0-10V	EM1 ¹ 8W EM Backup
	F Plaster		12 1250 lm	S Sunset	EM2 ² 12W EM Backup
	R Remodel		16 1600 lm	L2 Lutron	
	T Retrofit Kit		20 2000 lm		
			30 3000 lm		
					¹ Up to 700 lm output ² Up to 1100 lm output

STEP 2. Specify Laurel LED Light Engine part number (Select one) Example: E410L2030W2


4" ROUND LED LIGHT ENGINES

ITEM	STYLE		LUMENS	COLOR TEMP.	FINISH	GENERATION	BEAM ANGLE
E4							
E4	10L	Reflector	08 850 lm (12.6W MAX.)	27 ¹ 2700K	W All White	2 ³ Gen 2 Gen 1	60°
	11L	Wall Wash	12 1250 lm (16.8W MAX.)	30 3000K	B All Black		-F ¹ 38°
	12L	Drop Glass	16 1600 lm (21W MAX.)	35 3500K	C All Chrome		-N ¹ 24°
			20 2000 lm (29.4W MAX.)	40 4000K	H2 All Haze		-S ¹ 15°
			30 3000 lm (44.1W MAX.)	50 5000K	HW Haze with White Trim		
				SD ^{1,2} Sunset			
			¹ Available for lumen packages up to 3000 lm only ² Available with Generation 1 only		³ Not available for SD option	¹ Available for lumen packages up to 3000 lm only	

PRODUCT DIMENSIONS

LAUREL IC AIRTIGHT RECESSED HOUSINGS AND FRAMES

E4LH
NEW CONSTRUCTION ARCHITECTURAL FRAME WITH DRIVER



4 1/4"


11 1/2"

12"

4 3/4"

Hangar bars sold separately

E4LF
NEW CONSTRUCTION PLASTER FRAME WITH DRIVER




3 1/2"

8"

12 1/2"

4 7/8"

E4LR
REMODEL FRAME WITH DRIVER




6 1/2"

5 3/8"

12 1/2"

4 7/8"

E4LT
RETROFIT KIT WITH DRIVER




3 1/2"

4 7/8"

3"

LAUREL ACCESSORIES


CH26
C-CHANNEL BARS FOR COMMERCIAL HOUSINGS, T-BAR CEILING



1 1/2"

26"


FB27
FLAT BARS FOR COMMERCIAL FRAMES - WOOD CONSTRUCTION



1/2"

27"

KEM-LD1, KEM-LD2
EMERGENCY BATTERY BACKUP



4 1/2"

2 3/4"


11 1/8"

9 15/16"

2 5/8"

2'

KEM-LD3, LEM-LD4
EMERGENCY BATTERY BACKUP



4 1/2"

2 3/4"

11 1/8"


9 15/16"

2 5/8"

2'

PRODUCT DIMENSIONS

LAUREL™ LED LIGHT ENGINES



H (All Haze)



W (White)





B (Black)




C (Chrome)




HW (Haze w/White Trim)



H (All Haze)




W (White)




B (Black)




C (Chrome)



HW (Haze w/White Trim)



H (All Haze)



W (White)



B (Black)



C (Chrome)



HW (Haze w/White Trim)

TECHNICAL DETAILS

Optics:

Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED technology.

Construction (Housing and Frame): Constructed from 16 gauge galvanized steel for large architectural and commercial building applications.

Construction (Reflector): Reflector is one piece, deep, self-flanged construction spun from .05" thick High Grade Aluminum. Reflector allows for minimal glare and a strong glare cut-off. Wall wash reflector pushes light in one direction to evenly light up a wall or frame. Drop glass helps to virtually eliminate glare.

Installation (Housing and Frame): Designed for architectural buildings. Easily installed with hanger bars (ordered separately for specific application type). Light engine installed into frame. High-strength hanger bars can easily be nailed to joists. Suitable for T-grid and drop ceiling applications. Remodel clips hold housing sturdily into place. See installation sheet for detailed information.

Installation (Light Engine): Must be installed on a Laurel System frame with compatible lumen rating. Frames are available for New Construction, Remodel, and as a Retrofit Kit.

Junction Box: Positioned to accommodate straight conduit runs. Seven 1/2" trade size conduit knockouts and four pry-out knockout slots for easy Romex installation.

Hanger Bars: Hanger bars ordered separately for architectural frame as FB27: Set of two 27" hanger bars for wood construction. CH26: Set of two 26" C-Channel hanger bars for T-Bar Ceiling. Pre-installed hanger bars with True Nail for easy installation in regular lumber, engineered lumber, and laminated beams. Integral T-bar slots for easy installation in T-Bars. Spans up to 24" and can be repositioned 90°. Score lines allow for tool-free hanger bar size reduction. Integral leveling flange allows for single-person installation while easily aligning the housings with the joists.

Electrical:

Driver is rated for 120 - 277V input (120/277V).

High-efficiency driver with a power factor > 0.9.

Can be specified with Lutron drivers for specific applications.

Dimmability:

3-in-1 dimming: Triac, ELV, and 0-10V dimming, down to 1%.

Flicker-Free Dimming.

For a full list of dimmers, refer to the Dimmer Compatibility List.

LED Technology:

Extremely accurate Color Rendering Index of 93+ CRI.

Efficacy of >90 lumens per watt.

Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.

Superior Thermal Management by utilizing ELCO Red heat sink.

Instant On to Full Brightness technology.

No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology, be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings (Housing and Frame): cULus Listed for Damp Location. cULus Listed for Wet Location with select trims. cULus Listed for Direct Contact with Insulation and Combustible Material for units up to 1600 lm. cULus Listed for Feed Through.

Warranty:

ELCO Products are built to last. 5-year Limited warranty.

DIMMER COMPATIBILITY CHART

FOR REFERENCE ONLY

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility. The listed values were measured under ideal conditions in a test lab. Results in the field may differ.

MANUFACTURER	PRODUCT	PART NUMBER	DIMMED LIGHT OUTPUT RANGE
Triac/ELV Type Dimmers - 120V Only - D Driver			
Lutron	120V AC, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	RRD-6CL	1% - 100%
	120V AC 60Hz, 150W LED/CFL/Incandescent/Halogen, Single Pole, 3-Way,	DVCL-153P	1% - 100%
	120V 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	TGCL-153P	1% - 100%
	120V AC 60Hz, 300W Electronic Low Voltage, 3-Way, Commercial/Residential Application	DVELV-303P	1% - 100%
	120V, 600W Incandescent/Halogen, Single Pole, Residential Indoor Application	TG-600P	1% - 100%
	120V, 1000W Incandescent or 600W Magnetic Low Voltage, Single Pole, 3-Way	CT103P	1% - 100%
	120V AC 60Hz, 600W Electronic Low Voltage, Single Pole/Multi-Location	MAELV600	1% - 100%
	120V AC 60Hz, 500W Electronic Low Voltage, Single Pole/Multi-Location	FAELV500	1% - 100%
	120V AC 60Hz, 600W Incandescent/Halogen, Single Pole, Slide-to-Off Dimmer	S-600P	1% - 100%
	120V AC 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	SCL-153P	1% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	1% - 100%
	120V AC 60Hz, Low Voltage Load Type, 150W Single Pole	DVLV-600P	5% - 100%
	120V AC, 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way, Residential and Commercial Application	DV-603P	1% - 100%
	120V AC, 50/60Hz, 150W LED/CFL, 600W Incandescent/Halogen, Single Pole, 3-Way, Indoor Application	MA-PRO	1% - 100%
	120V AC 60Hz, 150W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way,	MACL-153M	1% - 100%
Leviton	120V AC 60Hz, 300W Electronic Low Voltage, 400 Volt Amp, Single Pole, 3-Way	IPE04	1% - 100%
	120V AC 60Hz, 300W CFL or 600W Incandescent, 400 Volt Amp, Single Pole, 3-Way	6673-10W	1% - 100%
	120V AC, 600W Incandescent with LED Locator, Single Pole, 3-Way	VP106	1% - 100%
	120V AC 60Hz, 500W Incandescent with LED Level Indicator, Single Pole, 3-Way	6161	1% - 100%
	120V AC, 150W LED/CFL or 600W Incandescent, Single Pole, 3-Way	6674	1% - 100%
Eaton	120V AC, 300W LED/CFL or 600W Incandescent/MLV/Halogen, Single Pole, 3-Way	TAL06P1-C1	1% - 100%
Cooper	120V AC 60Hz, 300W LED/CFL or 600W Incandescent/Halogen, Single Pole, 3-Way	SLC03P / DAL06P	1% - 100%
	120V AC 60Hz, 300W LED/CFL or 600W Incandescent, Single Pole, 3-Way	DLC03P	1% - 100%
	120V AC 60Hz, 600W Incandescent/Halogen, Single Pole, 3-Way,	RI061-VW-K2	1% - 100%
	120V AC 60Hz, 300W LED/CFL/ Incandescent/Halogen, Single Pole, 3-Way	AAL06A-C2	1% - 100%
Lightolier	120V, 260W Incandescent/Halogen, Single Pole, 3-Way	ZP260QEW	1% - 100%
0-10V Type Dimmers - 120/277V			
Lutron	120/277V AC, 0-10V LED/CFL Ballast, Single Pole, 3-Way	NFTV	1% - 100%
	120/277V AC, 0-10V, Single Pole, 3-Way, Commercial and Residential, Indoor Application	DVSTV	1% - 100%
	120/277V AC 50/60Hz, 0-10V LED/CFL Ballast, Single Pole, 3-Way, Indoor Application	DVTV	1% - 100%
Leviton	120/277V AC 60Hz, 0-10V LED/CFL Ballast, Single Pole, 3-Way	IP710-DL	1% - 100%


***NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



4" LAUREL™ ARCHITECTURAL REFLECTOR LED LIGHT ENGINE

PHOTOMETRIC REPORT	CANDLE POWER SUMMARY		ILLUMINANCE AT A DISTANCE		
Product #: E410L1235 Wattage / Lumens: 12.8W / 1166.6 lm Luminaire LPW: 91.1 lm/W 	Degress Vertical	0°	Distance to Target Plane	Center Beam Footcandles	Beam Diameter
	0	1617	4'	101	4.0'
	5	1591	6'	44.9	6.0'
	15	1294	8'	25.3	8.0'
	25	885	10'	16.2	10.0'
	35	324	ZONAL LUMEN SUMMARY		
	45	56			
	55	1	Zone	Lumens	%Luminaire
	65	1	0-30°	902.2	77.3
	75	0	0-40°	1,113.4	95.4
	85	0	0-60°	1,165.4	99.9
	90	0	0-90°	1,166.6	100